

The governing equations for CM1

George H. Bryan

National Center for Atmospheric Research, Boulder, Colorado, USA

email: `gbryan@ucar.edu`

Version 9

last modified: 20 June 2017

Copyright © 2011–2017 by George H. Bryan

All rights reserved.

1 Introduction

This document describes the governing equations for the CM1 numerical model, valid for release 19 (`cm1r19`; June 2017). This document is being provided because changes have occurred since the original release of the model (`cm1r1`, January 2003), which was described by Bryan (2002) and Bryan and Fritsch (2002). Differences in the governing equations between `cm1r1` and `cm1r19` are mostly minor; however, this document is being provided for clarity and also to provide details that are not available in the two articles cited above.

Definitions of many symbols are provided in Table 1 (for variables that are arrays in the code) and Table 2 (for variables that are constants in the code).

2 Governing equations

CM1 (“Cloud Model 1”) integrates governing equations for u , v , w , π' , θ' , and q_χ , where $\pi \equiv (p/p_{00})^{R/c_p}$ is a nondimensional pressure, and q_χ ($\chi = v, l, i$) represents the mixing ratios of moisture variables: q_v is water vapor mixing ratio; q_l is the mixing ratio of liquid water; and q_i is the mixing ratio of solid water (ice). Herein, a superscript prime denotes the perturbation from a base-state value. A base-state variable, by definition, is invariant in time and is a function of z only, and is denoted herein by a subscript 0. Thus, a generic variable α may be defined as follows: $\alpha(x, y, z, t) = \alpha_0(z) + \alpha'(x, y, z, t)$. The base state is further assumed to be in hydrostatic balance,

$$\frac{d\pi_0}{dz} = -\frac{g}{c_p\theta_{\rho 0}}, \quad (1)$$

where θ_ρ is density potential temperature,

$$\theta_\rho = \theta \left(\frac{1 + q_v/\varepsilon}{1 + q_v + q_l + q_i} \right). \quad (2)$$

The equation of state is

$$p = \rho RT (1 + q_v/\varepsilon), \quad (3)$$

or, because $T = \theta\pi$, the equation of state may be equivalently stated as,

$$\pi = \left(\frac{\rho R \theta (1 + q_v/\varepsilon)}{p_{00}} \right)^{\frac{R}{c_v}}. \quad (4)$$

Note that base state variables must also obey the equation of state. Herein, ρ represents the density of dry air.

The governing equations for velocity are

$$\frac{\partial u}{\partial t} + c_p \theta_\rho \frac{\partial \pi'}{\partial x} = \text{ADV}(u) + fv + T_u + D_u + N_u \quad (5a)$$

$$\frac{\partial v}{\partial t} + c_p \theta_\rho \frac{\partial \pi'}{\partial y} = \text{ADV}(v) - fu + T_v + D_v + N_v \quad (5b)$$

$$\frac{\partial w}{\partial t} + c_p \theta_\rho \frac{\partial \pi'}{\partial z} = \text{ADV}(w) + B + T_w + D_w + N_w \quad (5c)$$

where ADV is the advection operator, formulated in CM1 for a generic variable α as

$$\begin{aligned} \text{ADV}(\alpha) &= -u \frac{\partial \alpha}{\partial x} - v \frac{\partial \alpha}{\partial y} - w \frac{\partial \alpha}{\partial z} \\ &= \frac{1}{\rho_0} \left[-\frac{\partial(\rho_0 u \alpha)}{\partial x} - \frac{\partial(\rho_0 v \alpha)}{\partial y} - \frac{\partial(\rho_0 w \alpha)}{\partial z} \right. \end{aligned} \quad (6)$$

$$\left. + \alpha \left(\frac{\partial(\rho_0 u)}{\partial x} + \frac{\partial(\rho_0 v)}{\partial y} + \frac{\partial(\rho_0 w)}{\partial z} \right) \right], \quad (7)$$

B is buoyancy,

$$B = g \frac{\theta_\rho - \theta_{\rho 0}}{\theta_{\rho 0}} \cong g \left[\frac{\theta'}{\theta_0} + \left(\frac{1}{\varepsilon} - 1 \right) (q_v - q_{v,0}) - q_l - q_i \right], \quad (8)$$

and where T terms represent tendencies from turbulence (see Section 4), the D terms represent optional tendencies from other diffusive processes (discussed at the end of this section), and N represents Newtonian relaxation (i.e., Rayleigh damping). An f-plane is assumed when Coriolis acceleration is included (`icor` = 1).

The governing equations for the three moisture components are

$$\frac{\partial q_v}{\partial t} = \text{ADV}(q_v) + T_{q_v} + D_{q_v} - \dot{q}_{\text{cond}} - \dot{q}_{\text{dep}}, \quad (9a)$$

$$\frac{\partial q_l}{\partial t} = \text{ADV}(q_l) + T_{q_l} + D_{q_l} + \dot{q}_{\text{cond}} - \dot{q}_{\text{frz}} + \frac{1}{\rho} \frac{\partial(\rho V_l q_l)}{\partial z}, \quad (9b)$$

$$\frac{\partial q_i}{\partial t} = \text{ADV}(q_i) + T_{q_i} + D_{q_i} + \dot{q}_{\text{dep}} + \dot{q}_{\text{frz}} + \frac{1}{\rho} \frac{\partial(\rho V_i q_i)}{\partial z}. \quad (9c)$$

The \dot{q} terms represent phase changes between these three components, the T terms represent

tendencies from subgrid turbulence (see Section 4), D represents other optional diffusive tendencies (see final paragraph of this section). The last term on the right sides of (9b) and (9c) represents hydrometeor fallout by a terminal fall velocity (V , which is assumed to be positive-definite).

The governing equation for θ' is

$$\begin{aligned} \frac{\partial \theta'}{\partial t} = & \text{ADV}(\theta) - \Theta_1 \theta \left(\frac{\partial u}{\partial x} + \frac{\partial v}{\partial y} + \frac{\partial w}{\partial z} \right) + T_\theta + D_\theta + N_\theta \\ & + \Theta_2 (L_v \dot{q}_{\text{cond}} + L_s \dot{q}_{\text{dep}} + L_f \dot{q}_{\text{frz}}) + \Theta_3 (\dot{q}_{\text{cond}} + \dot{q}_{\text{dep}}) + \Theta_2 \epsilon + \dot{Q}_\theta + W_T \end{aligned} \quad (10)$$

where T_θ is the tendency from subgrid turbulence (see Section 4), D_θ represents optional diffusive tendencies (discussed at the end of this section), and term \dot{Q}_θ represents external tendencies to internal energy (primarily radiative heating/cooling). The N_θ term represents the tendency from Newtonian relaxation (i.e., Rayleigh damping), and the W_T term represents the cooling/warming effect from hydrometeors that fall relative to air (i.e., when $V_x \neq 0$); most numerical models neglect this effect but it is available in CM1 by setting `efall` = 1. The term with ϵ in (10) is associated with dissipative heating, which is the increase in internal energy that occurs when kinetic energy is dissipated; many numerical models neglect this effect but it is available in CM1 by setting `idiss` = 1.

The governing equations for π' is

$$\begin{aligned} \frac{\partial \pi'}{\partial t} = & \text{ADV}(\pi) - \Pi_1 \pi \left(\frac{\partial u}{\partial x} + \frac{\partial v}{\partial y} + \frac{\partial w}{\partial z} \right) + \Pi_2 (L_v \dot{q}_{\text{cond}} + L_s \dot{q}_{\text{dep}} + L_f \dot{q}_{\text{frz}}) \\ & + \Pi_3 (\dot{q}_{\text{cond}} + \dot{q}_{\text{dep}}) + \Pi_4 \left(T_\theta + D_\theta + N_\theta + \Theta_2 \epsilon + \dot{Q}_\theta + W_T \right) + \Pi_5 (T_{qv} + D_{qv}). \end{aligned} \quad (11)$$

In (10) and (11), the variables Θ and Π depend on the value chosen for `eqtset`, and determines whether the equation set mathematically conserves mass and energy in moist

environments. For dry environments (`imoist=0`) and for `eqtset=0`:

$$\Theta_1 = 0, \quad \Theta_2 = \frac{1}{c_p \pi}, \quad \Theta_3 = 0, \quad (12)$$

$$\Pi_1 = \frac{R}{c_v}, \quad \Pi_2 = \Pi_3 = \Pi_4 = \Pi_5 = 0. \quad (13)$$

This option yields the traditional (nonconservative) equation set that is used in many compressible nonhydrostatic models (such as ARPS, MM5, and the Klemp-Wilhelmson Model). The governing equation for θ under this option is equivalent to the one used in the Advanced Research WRF Model (ARW).

For `eqtset = 1`:

$$\Theta_1 = \left(\frac{R_m}{c_{vm}} - \frac{R c_{pm}}{c_p c_{vm}} \right), \quad \Theta_2 = \frac{c_v}{c_{vm} c_p \pi}, \quad \Theta_3 = -\theta \frac{R_v}{c_{vm}} \left(1 - \frac{R c_{pm}}{c_p R_m} \right), \quad (14)$$

$$\begin{aligned} \Pi_1 &= \frac{R c_{pm}}{c_p c_{vm}}, & \Pi_2 &= \frac{R}{c_p} \left(\frac{1}{c_{vm} \theta} \right), & \Pi_3 &= -\frac{R}{c_p} \left(\pi \frac{R_v c_{pm}}{R_m c_{vm}} \right), \\ \Pi_4 &= \frac{R \pi}{c_v \theta}, & \Pi_5 &= \frac{R \pi}{c_v \epsilon + q_v}. \end{aligned} \quad (15)$$

where

$$c_{pm} = c_p + c_{pv} q_v + c_l q_l + c_i q_i, \quad c_{vm} = c_v + c_{vv} q_v + c_l q_l + c_i q_i, \quad R_m = R + R_v q_v. \quad (16)$$

This option yields the mass- and energy-conserving equations of Bryan and Fritsch (2002). Note that (14) reduces to (12) and (15) reduces to (13) by setting $c_{pv} = c_{vv} = c_l = c_i = R_v = \Pi_2 = \Pi_3 = \Pi_4 = \Pi_5 = 0$.

The latent heats, L , are temperature-dependent according to Kirchoff's relations,

$$\frac{DL_v}{DT} = c_{pv} - c_l, \quad \frac{DL_s}{DT} = c_{pv} - c_i, \quad \frac{DL_f}{DT} = c_l - c_i. \quad (17)$$

Numerical values for L_v and L_s are obtained by integration of Kirchoff's relations using reference values $L_v(T_0)$ and $L_s(T_0)$ (see Table 2), and $L_f = L_s - L_v$.

The equations in this section are presented in the exact form that they are integrated in CM1 code. Users should be able to compare directly equations written herein with CM1 code. Note, however, that equations for the axisymmetric version of the model are slightly different; details can be found in Bryan and Rotunno (2009).

Finally, the optional diffusive tendencies represented by D terms above are excluded from most simulations. They can include sixth-order diffusion (`idiff=1` with `difforder=6`) which is sometimes used to filter small-scale fluctuations smaller than ≈ 6 times the grid spacing (e.g., Bryan 2005; Knievel et al. 2007). For very idealized simulations, second-order diffusion can be applied on coordinate surfaces (`idiff=1` with `difforder=2`).

3 Terrain

CM1 uses terrain-following coordinates, following Gal-Chen and Somerville (1975). The nominal heights of the coordinate surfaces are given by

$$\sigma = \frac{z_t(z - z_s)}{z_t - z_s} \quad (18)$$

where $z_s(x, y)$ is the terrain elevation, and z_t is the constant height of the model top. The following metric terms are used in CM1 to account for the coordinate transformation:

$$\begin{aligned} G_x &= \frac{\partial \sigma}{\partial x} = \frac{\sigma - z_t}{z_t - z_s} \frac{\partial z_s}{\partial x} \\ G_y &= \frac{\partial \sigma}{\partial y} = \frac{\sigma - z_t}{z_t - z_s} \frac{\partial z_s}{\partial y} \\ G_z &= \frac{\partial \sigma}{\partial z} = \frac{z_t}{z_t - z_s}. \end{aligned} \quad (19)$$

Horizontal gradients in Cartesian space (e.g., $\partial/\partial x|_z$) can be calculated from gradients along the terrain-following computational coordinates ($\partial/\partial x|_\sigma$) plus “correction terms” as follows:

$$\begin{aligned}\frac{\partial\alpha}{\partial x}\Big|_z &= G_z \frac{\partial}{\partial x} \left(\frac{\alpha}{G_z} \right) \Big|_\sigma + \frac{\partial}{\partial\sigma} (G_x\alpha) \\ \frac{\partial\alpha}{\partial y}\Big|_z &= G_z \frac{\partial}{\partial y} \left(\frac{\alpha}{G_z} \right) \Big|_\sigma + \frac{\partial}{\partial\sigma} (G_y\alpha).\end{aligned}\quad (20)$$

Vertical gradients are calculated simply by

$$\frac{\partial\alpha}{\partial z} = G_z \frac{\partial\alpha}{\partial\sigma}.\quad (21)$$

For the normal component of velocity to vanish at the surface, the following must hold:

$$w = u \frac{\partial z_s}{\partial x} + v \frac{\partial z_s}{\partial y} \quad \text{at} \quad \sigma = 0.\quad (22)$$

From (19) and (22) it follows that

$$\dot{\sigma} \equiv uG_x/G_z + vG_y/G_z + w = 0 \quad \text{at} \quad \sigma = 0.\quad (23)$$

Further, it is convenient to formulate the advection operator (6) for simulations with terrain as follows:

$$\begin{aligned}\text{ADV}(\alpha) = \frac{G_z}{\rho_0} \left[- \frac{\partial(\alpha\rho_0 u/G_z)}{\partial x} \Big|_\sigma - \frac{\partial(\alpha\rho_0 v/G_z)}{\partial y} \Big|_\sigma - \frac{\partial(\alpha\rho_0 \dot{\sigma})}{\partial\sigma} \right. \\ \left. + \alpha \left(\frac{\partial(\rho_0 u/G_z)}{\partial x} \Big|_\sigma + \frac{\partial(\rho_0 v/G_z)}{\partial y} \Big|_\sigma + \frac{\partial(\rho_0 \dot{\sigma})}{\partial\sigma} \right) \right].\end{aligned}\quad (24)$$

4 Turbulence

If $\text{cm1setup} \geq 1$ then tendencies due to small-scale turbulence and/or molecular-scale diffusion (represented generically by the T terms in Section 2) are formulated as follows:

$$T_u = \frac{1}{\rho} \left[\frac{\partial \tau_{11}}{\partial x} + \frac{\partial \tau_{12}}{\partial y} + \frac{\partial \tau_{13}}{\partial z} \right] \quad (25)$$

$$T_v = \frac{1}{\rho} \left[\frac{\partial \tau_{12}}{\partial x} + \frac{\partial \tau_{22}}{\partial y} + \frac{\partial \tau_{23}}{\partial z} \right] \quad (26)$$

$$T_w = \frac{1}{\rho} \left[\frac{\partial \tau_{13}}{\partial x} + \frac{\partial \tau_{23}}{\partial y} + \frac{\partial \tau_{33}}{\partial z} \right] \quad (27)$$

$$T_s = -\frac{1}{\rho} \left[\frac{\partial \tau_1^s}{\partial x} + \frac{\partial \tau_2^s}{\partial y} + \frac{\partial \tau_3^s}{\partial z} \right] \quad (28)$$

where s represents one of the model scalars (θ , q_v , q_l , or q_i). The subgrid stress terms (τ_{ij}) are formulated as follows:

$$\tau_{ij} \equiv \overline{\rho u'_i u'_j} = 2\rho K_m S_{ij}, \quad (29)$$

where K_m is viscosity (explained below) and S_{ij} is the strain tensor,

$$S_{ij} = \frac{1}{2} \left(\frac{\partial u_i}{\partial x_j} + \frac{\partial u_j}{\partial x_i} \right). \quad (30)$$

The turbulent fluxes for scalars are

$$\tau_i^\theta \equiv \overline{\rho u'_i \theta'} = -K_h \rho \frac{\partial \theta}{\partial x_i}, \quad (31)$$

$$\tau_i^{q_v} \equiv \overline{\rho u'_i q'_v} = -K_h \rho \frac{\partial q_v}{\partial x_i}, \quad (32)$$

$$\tau_i^{q_l} \equiv \overline{\rho u'_i q'_l} = -K_h \rho \frac{\partial q_l}{\partial x_i}, \quad (33)$$

$$\tau_i^{q_i} \equiv \overline{\rho u'_i q'_i} = -K_h \rho \frac{\partial q_i}{\partial x_i}, \quad (34)$$

where K_h is diffusivity (see below). The relations (29) and (31)–(34) apply to the interior of a model domain; different formulations are applied on boundaries to account for surface

stress (i.e., drag) and fluxes of temperature and moisture.

The method to determine K_m and K_h depends on the setup of CM1. For `cm1setup=0`, $K_m = K_h = 0$, so all T terms in Section 2 are set to zero. The methods for `cm1setup` ≥ 0 are described below.

4.1 Large-Eddy Simulation (LES) (`cm1setup=1`)

For `cm1setup = 1` a large-eddy simulation (LES) closure is used. Three different approaches are currently available in CM1, depending on the setting for the subgrid-scale model (`sgsmodel`).

4.1.1 No subgrid model for interior flow (`sgsmodel=0`)

With `sgsmodel=0` the stress terms (τ_{ij}) and flux terms (e.g., τ_i^θ , τ_i^{qv} , etc.) are set to zero *except* at the lower and upper boundaries. Thus, no subgrid-scheme model is used in the interior of the model domain, but boundary conditions are set consistently with LES methods. The tendency terms (T) are generally zero except near the upper and lower boundaries.

4.1.2 TKE scheme (`sgsmodel=1`)

With `sgsmodel=1` a subgrid turbulence kinetic energy (TKE) is predicted and used to determine K_m and K_h . The scheme in CM1 is similar to that described by Deardorff (1980). The eddy viscosity K_m is determined from the relation

$$K_m = c_m l e^{1/2}. \quad (35)$$

and the eddy diffusivity K_h is determined from the relation

$$K_h = c_h l e^{1/2}, \quad (36)$$

where $e = \frac{1}{2}\overline{u'_i u'_i}$ is the subgrid TKE. The predictive equation for e is

$$\frac{\partial e}{\partial t} = \text{ADV}(e) + K_m S^2 - K_h N_m^2 + \frac{1}{\rho} \frac{\partial}{\partial x_i} \left(2\rho K_m \frac{\partial e}{\partial x_i} \right) - \epsilon \quad (37)$$

where ϵ is dissipation, which is parameterized as

$$\epsilon = c_\epsilon e^{3/2}/l, \quad (38)$$

and S^2 is deformation,

$$S^2 = 2S_{ij}S_{ij}. \quad (39)$$

N_m^2 is the squared Brunt-Väisälä frequency, which for subsaturated air is given by

$$N_m^2 = \frac{g}{\theta_\rho} \frac{\partial \theta_\rho}{\partial z}, \quad (40)$$

and for saturated air is given by

$$N_m^2 = \frac{g}{T} \left(\frac{\partial T}{\partial z} + \Gamma_m \right) \left(1 + \frac{T}{\varepsilon + q_s} \frac{\partial q_s}{\partial T} \right) - \frac{g}{1 + q_t} \frac{\partial q_t}{\partial z}, \quad (41)$$

where q_s is saturation mixing ratio, Γ_m is the moist-adiabatic lapse rate,

$$\Gamma_m = g(1 + q_t) \left(\frac{1 + L_v q_s / RT}{c_{pm} + L_v \partial q_s / \partial T} \right). \quad (42)$$

and $q_t = 1 + q_v + q_l + q_i$ is the total water mixing ratio.

The parameters c_m , c_h , c_ϵ , and l must be specified to close these equations. In CM1, the default value for c_m is 0.10. The parameters c_h , c_ϵ , and l have a stability dependence that is designed to reduce subgrid-scale mixing in statically stable conditions (i.e., for $N_m^2 > 0$).

The default formulation in CM1 is as follows:

$$c_h = 1 + 2 \frac{l}{\Delta} \quad (43)$$

$$c_\epsilon = 0.2 + 0.787 \frac{l}{\Delta} \quad (44)$$

$$l = \left(\frac{2}{3} \frac{e}{N_m^2} \right)^{1/2}, \quad (45)$$

where Δ is a measure of the grid size, e.g.,

$$\Delta = (\Delta x \Delta y \Delta z)^{1/3}. \quad (46)$$

Note that $l = \Delta$ when $N_m^2 \leq 0$. The settings for c_m , c_ϵ , and l in CM1 ensure that turbulence is inactive (i.e., $K_m = K_h = 0$) when $\text{Ri} > 0.25$, where Ri is the Richardson number,

$$\text{Ri} = \frac{N_m^2}{S^2}. \quad (47)$$

4.1.3 Smagorinsky scheme (sgsmodel=2)

For `sgsmodel = 2` a simpler scheme is used. By assuming steady and homogeneous subgrid turbulence, and by neglecting the stability dependence of the parameters discussed in the previous subsection, then the following relation can be derived:

$$K_m = (C_s \Delta)^2 \left[S^2 \left(1 - \frac{\text{Ri}}{\text{Pr}} \right) \right]^{1/2}, \quad (48)$$

where $C_s = (c_m/\pi)^{1/2} = 0.178$ is the Smagorinsky constant [after Smagorinsky (1963)] and $\text{Pr} \approx 1/3$ is the Prandtl number. The eddy diffusivity is given by

$$K_h = K_m/\text{Pr}. \quad (49)$$

If $Ri > Pr$ in (48) then K_m is set to zero; hence, subgrid turbulence is active (i.e., $K_m > 0$) only when $Ri < Pr$.

Compared to the TKE scheme, the Smagorinsky scheme has three primary disadvantages: 1) Subgrid turbulence for the Smagorinsky scheme is active (i.e., $K_m > 0$) only when $S^2 > 0$ (i.e., in locally sheared conditions). 2) The assumption of steady and homogeneous turbulence inherent in the Smagorinsky scheme is a major disadvantage in some situations, particularly when resolution is poor. 3) As formulated, there is no stability dependence to the inherent length scales in this Smagorinsky scheme, which makes it too diffusive in stable conditions ($N_m^2 > 0$). This last deficiency can be alleviated (see, e.g., Stevens et al. 1999), and might be addressed in a future version of CM1.

4.2 Mesoscale modeling / Planetary Boundary Layer (PBL) parameterization (cm1setup=2)

For `cm1setup = 2`, it is assumed that no turbulent eddies are resolved on the grid, and hence their effects must be accounted completely via the T terms in section 2. The schemes in CM1 use slightly different forms of (29) and (31)–(34):

$$\begin{aligned} \tau_{11} &= 2\rho K_{m,h} \frac{\partial u}{\partial x}, & \tau_{22} &= 2\rho K_{m,h} \frac{\partial v}{\partial y}, & \tau_{33} &= 2\rho K_{m,h} \frac{\partial w}{\partial z}, \\ \tau_{12} &= \rho K_{m,h} \left(\frac{\partial u}{\partial y} + \frac{\partial v}{\partial x} \right), & \tau_{13} &= \rho K_{m,v} \left(\frac{\partial u}{\partial z} + \frac{\partial w}{\partial x} \right), & \tau_{23} &= \rho K_{m,v} \left(\frac{\partial v}{\partial z} + \frac{\partial w}{\partial y} \right), \\ \tau_1^s &= -\rho K_{h,h} \frac{\partial s}{\partial x}, & \tau_2^s &= -\rho K_{h,h} \frac{\partial s}{\partial y}, & \tau_3^s &= -\rho K_{h,v} \frac{\partial s}{\partial z}. \end{aligned} \quad (50)$$

4.2.1 Horizontal turbulence scheme (horizturb = 1)

For `horizturb = 1`, a simple scheme is used. This scheme is often called a “horizontal Smagorinsky scheme” in the literature. Here, a horizontal eddy viscosity is calculated,

$$K_{m,h} = l_h^2 S_h \quad (51)$$

where the horizontal deformation is:

$$S_h^2 = 2 \left(\frac{\partial u}{\partial x} \right)^2 + 2 \left(\frac{\partial v}{\partial y} \right)^2 + 2 \left(\frac{\partial w}{\partial z} \right)^2 + \left(\frac{\partial u}{\partial y} + \frac{\partial v}{\partial x} \right)^2. \quad (52)$$

The variable l_h is a horizontal length scale associated with turbulence, and must be set by the user (see variables `l_h`, `lhref1`, and `lhref2` in `README.namelist`). The diffusivity is the same as viscosity, i.e., $K_{h,h} = K_{m,h}$.

4.2.2 Vertical turbulence / PBL schemes (ipbl ≥ 1)

When `cm1setup = 2`, a Planetary Boundary Layer (PBL) parameterization may be used. For `ipbl = 1`, the Yonsei University (YSU) PBL scheme is used. This scheme is described in Hong et al. (2006). The YSU scheme is based on a K-Profile Parameterization (KPP) approach for the near-surface boundary layer, but includes an explicit treatment of entrainment at the top of the PBL (Hong et al. 2006).

When `ipbl = 2`, a Smagorinsky-type scheme is used in the vertical direction, where

$$K_{m,v} = l_v^2 S_v \left(1 - \frac{\text{Ri}}{\text{Pr}} \right)^{1/2} \quad (53)$$

where

$$S_v^2 = \left(\frac{\partial u}{\partial z} + \frac{\partial w}{\partial x} \right)^2 + \left(\frac{\partial v}{\partial z} + \frac{\partial w}{\partial y} \right)^2. \quad (54)$$

Since `cm1r17`, l_v is determined from the relation $l_v^{-2} = (\kappa z)^{-2} + l_\infty^{-2}$ where l_∞ is a specified asymptotic length scale far from the surface (see `l_inf` in `README.namelist`). The value for the Prandtl number `Pr` must be set to 1 by default.

4.3 Direct Numerical Simulation (`cm1setup=3`)

For `cm1setup=3`, the viscosity and diffusivity in (29) and (31)–(34) are set to constant values ($K_m = \text{viscosity}$; $K_h = \text{viscosity} / \text{pr_num}$).

5 Anelastic/incompressible equations

The equations in section 2 are used in CM1 when one of the compressible solvers are chosen (`psolver = 1,2,3`). CM1 also has the ability to use the anelastic equations (`psolver = 4`) and the incompressible equations (`psolver = 5`).

For the anelastic equations, the velocity equations can be written as:

$$\frac{\partial u}{\partial t} + \frac{\partial \phi}{\partial x} = F_u \quad (55a)$$

$$\frac{\partial v}{\partial t} + \frac{\partial \phi}{\partial y} = F_v \quad (55b)$$

$$\frac{\partial w}{\partial t} + \frac{\partial \phi}{\partial z} = F_w. \quad (55c)$$

where F_u , F_v , and F_w represent all terms on the right side of (5a), (5b), and (5c), respectively. Notice that the pressure-gradient terms are written in terms of $\phi \equiv p'/\rho_0$. There is no predictive equation for pressure in this system of equations. Hence, (11) is not integrated in the anelastic system. Instead, a diagnostic equation for ϕ is developed by using the anelastic mass-continuity equation,

$$\frac{\partial}{\partial x_i} (\rho_0 u_i) = 0. \quad (56)$$

Using (55) and (56), the diagnostic equation for ϕ is simply

$$\frac{\partial}{\partial x_i} \left(\rho_0 \frac{\partial \phi}{\partial x_i} \right) = \frac{\partial (\rho_0 F_u)}{\partial x} + \frac{\partial (\rho_0 F_v)}{\partial y} + \frac{\partial (\rho_0 F_w)}{\partial z}. \quad (57)$$

CM1 solves (57) using a direct method based on fast Fourier transforms. Because the anelastic equations do not permit acoustic waves, there is no need for small time steps.

The incompressible equations are the same as the anelastic equations except it is assumed that $\rho_0 = \text{constant}$. This system of equations is only appropriate for simulations with a shallow domain (of order 1 km or less).

6 Compressible-Boussinesq equations

Since cm1r18, there is an option to use the “compressible Boussinesq” equations (`psolver = 6`). In this equation set, the Boussinesq approximation has been made, in which density variations are neglected in the velocity equations (except where multiplied by gravity). Further, a prognostic “pressure” equation is used, and thus acoustic waves are permitted. The equations are as follows:

$$\frac{\partial u}{\partial t} = -u \frac{\partial u}{\partial x} - v \frac{\partial u}{\partial y} - w \frac{\partial u}{\partial z} - \frac{\partial \phi}{\partial x} + fv + T_u + D_u + N_u \quad (58)$$

$$\frac{\partial v}{\partial t} = -u \frac{\partial v}{\partial x} - v \frac{\partial v}{\partial y} - w \frac{\partial v}{\partial z} - \frac{\partial \phi}{\partial y} - fu + T_v + D_v + N_v \quad (59)$$

$$\frac{\partial w}{\partial t} = -u \frac{\partial w}{\partial x} - v \frac{\partial w}{\partial y} - w \frac{\partial w}{\partial z} - \frac{\partial \phi}{\partial z} + g \frac{\theta'}{\theta_0} + T_w + D_w + N_w \quad (60)$$

$$\frac{\partial \phi}{\partial t} = -c_s^2 \left(\frac{\partial u}{\partial x} + \frac{\partial v}{\partial y} + \frac{\partial w}{\partial z} \right). \quad (61)$$

In (61), c_s is a constant speed of sound that can be specified by the user; the default value is 300 m s⁻¹. These equations are most applicable to shallow flows (of order 1 km) and should only be used in similar situations as the incompressible equations. These equations are solved using the Klemp-Wilhelmson time-splitting scheme with explicit calculations in

both horizontal and vertical directions (the same as `psolver = 2`).

References

- Bryan, G. H., 2002: An investigation of the convective region of numerically simulated squall lines. Ph.D. dissertation, The Pennsylvania State University.
- Bryan, G. H., 2005: Spurious convective organization in simulated squall lines owing to moist absolutely unstable layers. *Mon. Wea. Rev.*, **133**, 1978–1997.
- Bryan, G. H., and J. M. Fritsch, 2002: A benchmark simulation for moist nonhydrostatic numerical models. *Mon. Wea. Rev.*, **130**, 2917–2928.
- Bryan, G. H., and R. Rotunno, 2009: The maximum intensity of tropical cyclones in axisymmetric numerical model simulations. *Mon. Wea. Rev.*, **137**, 1770–1789.
- Deardorff, J. W., 1980: Stratocumulus-capped mixed layer derived from a three-dimensional model. *Bound.-Layer Meteor.*, **18**, 495–527.
- Gal-Chen, T., and R. Somerville, 1975: On the use of a coordinate transformation for the solution of the Navier-Stokes equations. *J. Comput. Phys.*, **17**, 209–228.
- Hong, S.-Y., Y. Noh, and J. Dudhia, 2006: A new vertical diffusion package with an explicit treatment of entrainment processes. *Mon. Wea. Rev.*, **134**, 2318–2341.
- Knievel, J. C., G. H. Bryan, and J. P. Hacker, 2007: Explicit numerical diffusion in the WRF Model. *Mon. Wea. Rev.*, **135**, 3808–3824.
- Smagorinsky, J., 1963: General circulation experiments with the primitive equations. I. The basic experiment. *Mon. Wea. Rev.*, **91**, 99–164.
- Stevens, B., C.-H. Moeng, and P. P. Sullivan, 1999: Large-eddy simulations of radiatively driven convection: Sensitivities to the representation of small scales. *J. Atmos. Sci.*, **56**, 3963–3984.

Table 1: Variables and arrays in CM1.

Symbol	Description	Name in code
Predicted variables:		
q	Mixing ratio of moisture	qa (at t) q3d (at $t + \Delta t$)
u	Velocity in x	ua (at t) u3d (at $t + \Delta t$)
v	Velocity in y	va (at t) v3d (at $t + \Delta t$)
w	Velocity in z	wa (at t) w3d (at $t + \Delta t$)
θ_0	Base-state θ	th0
θ'	Perturbation θ	tha (at t) th3d (at $t + \Delta t$)
π_0	Base-state π	pi0
π'	Perturbation π	ppi (at t) pp3d (at $t + \Delta t$)
Derived variables:		
p	Pressure	prs
T	Temperature ($T = \theta\pi$)	varies
θ	Potential temperature ($\theta = \theta_0 + \theta'$)	varies
π	Nondimensional pressure ($\pi = \pi_0 + \pi'$)	varies
ρ	Density of dry air	rho
$\rho_0 u$	u multiplied by ρ_0	rru (if no terrain)
$\rho_0 v$	v multiplied by ρ_0	rrv (if no terrain)
$\rho_0 w$	w multiplied by ρ_0	rrw (if no terrain)
$\rho_0 u/G_z$	$\rho_0 u/G_z$	rru (if terrain)
$\rho_0 v/G_z$	$\rho_0 v/G_z$	rrv (if terrain)
$\rho_0 \dot{\sigma}$	$\rho_0 \dot{\sigma} = \rho_0 (uG_x/G_z + vG_y/G_z + w)$	rrw (if terrain)
Variables for terrain only:		
G_x	$\frac{\sigma - z_t}{z_t - z_s} \frac{\partial z_s}{\partial x}$	gx
G_y	$\frac{\sigma - z_t}{z_t - z_s} \frac{\partial z_s}{\partial y}$	gy
G_z	$\frac{z_t}{z_t - z_s}$	gz
z_s	Terrain height	zs
z_t	Height at top of domain	zt
σ	Nominal height of model levels, $\sigma = \frac{z_t(z - z_s)}{z_t - z_s}$	sigma

Table 2: Constants in CM1. See `constants.F` for values.

Symbol	Description	Name in code
c_i	Specific heat of ice	<code>cpi</code>
c_l	Specific heat of liquid water	<code>cpl</code>
c_p	Specific heat of dry air at constant pressure	<code>cp</code>
c_{pv}	Specific heat of water vapor at constant pressure	<code>cpv</code>
c_v	Specific heat of dry air at constant volume	<code>cv</code>
c_{vv}	Specific heat of water vapor at constant volume	<code>cvv</code>
f	Coriolis parameter	<code>fcor</code>
g	Gravitational acceleration	<code>g</code>
$L_v(T_0)$	Reference value of L_v at $T = T_0$	<code>xlv</code>
$L_s(T_0)$	Reference value of L_s at $T = T_0$	<code>xls</code>
p_{00}	Reference pressure	<code>p00</code>
R	Gas constant for dry air	<code>rd</code>
R_v	Gas constant for water vapor	<code>rv</code>
T_0	Reference temperature	<code>to</code>
ε	Ratio of gas constants: R/R_v	<code>eps</code>
κ	von Karman constant	<code>karman</code>

Table 3: Description of potential temperature (θ) “budget” variables in CM1 output.

Name in CM1 output	Budget term	Description
ptb_hadv	$-u \frac{\partial \theta}{\partial x} - v \frac{\partial \theta}{\partial y}$	horizontal advection
ptb_vadv	$-w \frac{\partial \theta}{\partial z}$	vertical advection
ptb_hturb	$-\frac{1}{\rho} \left[\frac{\partial \tau_1^\theta}{\partial x} + \frac{\partial \tau_2^\theta}{\partial y} \right]$ (part of T_θ)	horizontal turbulence tendency
ptb_vturb	$-\frac{1}{\rho} \left[\frac{\partial \tau_3^\theta}{\partial z} \right]$ (part of T_θ)	vertical turbulence tendency
ptb_mp	(see terms with \dot{q})	tendency from microphysical scheme
ptb_rdamp	N_θ	tendency from Rayleigh damping
ptb_rad	\dot{Q}_θ	tendency from radiation scheme
ptb_div	$-\Theta_1 \theta \left(\frac{\partial u}{\partial x} + \frac{\partial v}{\partial y} + \frac{\partial w}{\partial z} \right)$	moist divergence term
ptb_diss	$\Theta_2 \epsilon$	dissipative heating
ptb_pbl	(part of T_θ)	tendency from PBL scheme

Table 4: Description of water vapor mixing ratio (q_v) “budget” variables in CM1 output.

Name in CM1 output	Budget term	Description
qvb_hadv	$-u \frac{\partial q_v}{\partial x} - v \frac{\partial q_v}{\partial y}$	horizontal advection
qvb_vadv	$-w \frac{\partial q_v}{\partial z}$	vertical advection
qvb_hturb	$-\frac{1}{\rho} \left[\frac{\partial \tau_1^{q_v}}{\partial x} + \frac{\partial \tau_2^{q_v}}{\partial y} \right]$ (part of T_{q_v})	horizontal turbulence tendency
qvb_vturb	$-\frac{1}{\rho} \left[\frac{\partial \tau_3^{q_v}}{\partial z} \right]$ (part of T_{q_v})	vertical turbulence tendency
qvb_mp	(see terms with \dot{q})	tendency from microphysical scheme
qvb_pbl	(part of T_{q_v})	tendency from PBL scheme

Table 5: Description of horizontal velocity (u) “budget” variables in CM1 output.

Name in CM1 output	Budget term	Description
ub_hadv	$-u \frac{\partial u}{\partial x} - v \frac{\partial u}{\partial y}$	horizontal advection
ub_vadv	$-w \frac{\partial u}{\partial z}$	vertical advection
ub_hturb	$+\frac{1}{\rho} \left[\frac{\partial \tau_{11}}{\partial x} + \frac{\partial \tau_{12}}{\partial y} \right]$ (part of T_u)	horizontal turbulence tendency
ub_vturb	$+\frac{1}{\rho} \left[\frac{\partial \tau_{13}}{\partial z} \right]$ (part of T_u)	vertical turbulence tendency
ub_pgrad	$-c_p \theta_\rho \frac{\partial \pi'}{\partial x}$	pressure gradient acceleration
ub_rdamp	N_u	tendency from Rayleigh damping
ub_cor	fv	Coriolis acceleration
ub_cent	$\frac{vv}{r}$	centrifugal acceleration (for axisymm = 1)
ub_pbl	(part of T_u)	tendency from PBL scheme

Table 6: Description of horizontal velocity (v) “budget” variables in CM1 output.

Name in CM1 output	Budget term	Description
vb_hadv	$-u \frac{\partial v}{\partial x} - v \frac{\partial v}{\partial y}$	horizontal advection
vb_vadv	$-w \frac{\partial v}{\partial z}$	vertical advection
vb_hturb	$+\frac{1}{\rho} \left[\frac{\partial \tau_{12}}{\partial x} + \frac{\partial \tau_{22}}{\partial y} \right]$ (part of T_v)	horizontal turbulence tendency
vb_vturb	$+\frac{1}{\rho} \left[\frac{\partial \tau_{23}}{\partial z} \right]$ (part of T_v)	vertical turbulence tendency
vb_pgrad	$-c_p \theta_\rho \frac{\partial \pi'}{\partial y}$	pressure gradient acceleration
vb_rdamp	N_v	tendency from Rayleigh damping
vb_cor	$-fu$	Coriolis acceleration
vb_cent	$-\frac{uv}{r}$	centrifugal acceleration (for axisymm = 1)
vb_pbl	(part of T_v)	tendency from PBL scheme

Table 7: Description of horizontal velocity (w) “budget” variables in CM1 output.

Name in CM1 output	Budget term	Description
wb_hadv	$-u \frac{\partial w}{\partial x} - v \frac{\partial w}{\partial y}$	horizontal advection
wb_vadv	$-w \frac{\partial w}{\partial z}$	vertical advection
wb_hturb	$+\frac{1}{\rho} \left[\frac{\partial \tau_{13}}{\partial x} + \frac{\partial \tau_{23}}{\partial y} \right]$ (part of T_w)	horizontal turbulence tendency
wb_vturb	$+\frac{1}{\rho} \left[\frac{\partial \tau_{33}}{\partial z} \right]$ (part of T_w)	vertical turbulence tendency
wb_pgrad	$-c_p \theta_\rho \frac{\partial \pi'}{\partial z}$	pressure gradient acceleration
wb_rdamp	N_w	tendency from Rayleigh damping
wb_buoy	B	buoyancy