

WRF Registry and Examples

John Michalakes, NREL

Michael Duda, NCAR

Dave Gill, NCAR

[WRF Software Architecture Working Group](#)

Outline

- Registry Mechanics

- Examples


Introduction – Intended Audience

- Intended audience for this tutorial session: scientific users and others who wish to:
 - Understand **overall design** concepts and motivations
 - **Work** with the code
 - **Extend/modify** the code to enable their work/research
 - Address **problems** as they arise
 - Adapt the code to take advantage of **local computing** resources

Introduction – WRF Resources

- WRF project home page
 - <http://www.wrf-model.org>
- WRF users page (linked from above)
 - <http://www.mmm.ucar.edu/wrf/users>
- On line documentation (also from above)
 - http://www.mmm.ucar.edu/wrf/WG2/software_v2
- WRF user services and help desk
 - wrfhelp@ucar.edu

WRF Software Architecture



Registry

- Hierarchical software architecture
 - Insulate scientists' code from parallelism and other architecture/implementation-specific details
 - Well-defined interfaces between layers, and external packages for communications, I/O, and model coupling facilitates code reuse and exploiting of community infrastructure, e.g. ESMF.

WRF Registry

- "Active data-dictionary" for managing WRF data structures
 - Database describing attributes of model state, intermediate, and configuration data
 - Dimensionality, number of time levels, staggering
 - Association with physics
 - I/O classification (history, initial, restart)
 - Communication points and patterns
 - Configuration lists (e.g. namelists)
 - Nesting down-scale interpolation and up-scale feedback

WRF Registry

- "Active data-dictionary" for managing WRF data structures
 - Program for auto-generating sections of WRF from database:
 - 2000 - 3000 Registry entries \Rightarrow 300-thousand lines of automatically generated WRF code

```
cd frame
cat *.F | wc -l
    21558
cat *.f90 | wc -l
    250653
cd ../share
cat *.F | wc -l
    34040
cat *.f90 | wc -l
    124004
```

- Allocation statements for state data and I1 data
- Interprocessor communications: Halo and periodic boundary updates, transposes
- Code for defining and managing run-time configuration information
- Code for forcing, feedback, shifting, and interpolation of nest data

WRF Registry

- Why?
 - Automates time consuming, repetitive, error-prone programming
 - Insulates programmers and code from package dependencies
 - Allow rapid development
 - Documents the data
- A Registry file is available for each of the dynamical cores, plus special purpose packages
- Reference: Description of WRF Registry, http://www.mmm.ucar.edu/wrf/WG2/software_v2

Registry Data Base

- Currently implemented as a text file: *Registry/Registry.EM*
- Types of entry:
 - *Dimspec*— dimensions that are used to define arrays in the model
 - *State*— variables and arrays in the domain structure
 - */1*— local variables and arrays in solve, typically tendency values
 - *Typedef*— derived types that are subtypes of the domain structure

Registry Data Base

- Types of entry:
 - *Rconfig* — configuration (e.g. namelist) variable or array
 - *Package* — attributes of a package (e.g. physics)
 - *Halo* — interprocessor communications
 - *Period* — communications for periodic boundary updates
 - *Xpose* — communications for parallel matrix transposes
 - *Include* — similar to a CPP `#include` file

Registry State Entry

| # | Type | Sym | Dims | Use | Tlev | Stag | IO | Dname | Descrip |
|-------|------|-----|------|--------|------|------|-----------|-------|--------------------|
| state | real | u | ikjb | dyn_em | 2 | X | i01rhusdf | "U" | "X WIND COMPONENT" |

- Elements
 - *Entry*: The keyword “state”
 - *Type*: The type of the state variable or array (real, double, integer, logical, character, or derived)
 - *Sym*: The symbolic name of the variable or array
 - *Dims*: A string denoting the dimensionality of the array or a hyphen (-)
 - *Use*: A string denoting association with a solver or 4D scalar array, or a hyphen
 - *NumTLev*: An integer indicating the number of time levels (for arrays) or hyphen (for variables)

Registry State Entry

| # | Type | Sym | Dims | Use | Tlev | Stag | IO | Dname | Descrip |
|-------|------|-----|------|--------|------|------|-----------|-------|--------------------|
| state | real | u | ikjb | dyn_em | 2 | X | i01rhusdf | "U" | "X WIND COMPONENT" |

- Elements
 - *Stagger*: String indicating staggered dimensions of variable (X, Y, Z, or hyphen)
 - *IO*: String indicating whether and how the variable is subject to I/O and Nesting
 - *DName*: Metadata name for the variable
 - *Units*: Metadata units of the variable
 - *Descrip*: Metadata description of the variable

Registry State Entry

| # | Type | Sym | Dims | Use | Tlev | Stag | IO | Dname | Descrip |
|-------|------|-----|------|--------|------|------|-------------------|-------|--------------------|
| state | real | u | ikjb | dyn_em | 2 | X | i01rh <u>usdf</u> | "U" | "X WIND COMPONENT" |

- This single entry results in over 100 lines of code automatically added to more than 40 different locations in the WRF model, the real and ideal initialization programs, and in the WRF-Var package
- Nesting code to interpolate, force, feedback, and smooth u
- Addition of u to the input, restart, history, and LBC I/O streams

Registry State Entry

| # | Type | Sym | Dims | Use | Tlev | Stag | IO | Dname | Descrip |
|-------|------|-----|------|--------|------|------|-----------|-------|--------------------|
| state | real | u | ikjb | dyn_em | 2 | X | i01rhusdf | "U" | "X WIND COMPONENT" |

Declaration and dynamic allocation of arrays in TYPE(domain)

Two 3D state arrays corresponding to the 2 time levels of U

u_1 (ims:ime , kms:kme , jms:jme)

u_2 (ims:ime , kms:kme , jms:jme)

Eight LBC arrays for boundary and boundary tendencies

u_b[t][xy][se]

Example for boundary in the x-direction

u_bxse (jms:jme, kms:kme, spec_bdy_width, 4)

State Entry: Defining a variable-set for an I/O stream

- Fields are added to a variable-set on an I/O stream in two ways
 - At compile-time with Registry
 - At run-time with namelist option

| # | Type | Sym | Dims | Use | Tlev | Stag | IO | Dname | Descrip |
|-------|------|-----|------|--------|------|------|-----------|-------|--------------------|
| state | real | u | ikjb | dyn_em | 2 | X | i01rhusdf | "U" | "X WIND COMPONENT" |

IO is a string that specifies if the variable is to be subject to initial, restart, or history I/O. The string may consist of **'h'** (subject to history I/O), **'i'** (initial dataset), or **'r'** (restart dataset). The 'h', 'r', and 'i' specifiers may appear in any order or combination.

The 'h' and 'i' specifiers may be followed by an optional integer string consisting of '0', '1', ..., '9'. Zero denotes that the variable is part of the principal input or history I/O stream. The characters '1' through '9' denote one of the auxiliary input or history I/O streams.

usdf refers to nesting options: **u** = **UP**, **d** = **DOWN**, **s** = **SMOOTH**, **f** = **FORCE**

State Entry: Defining Variable-set for an I/O stream

irh -- The state variable will be included in the WRF model input, restart, and history I/O streams

irh13 -- The state variable has been added to the first and third auxiliary history output streams; it has been removed from the principal history output stream, because zero is not among the integers in the integer string that follows the character 'h'

rh01 -- The state variable has been added to the first auxiliary history output stream; it is also retained in the principal history output

i205hr -- Now the state variable is included in the principal input stream as well as auxiliary inputs 2 and 5. Note that the order of the integers is unimportant. The variable is also in the principal history output stream

ir12h -- No effect; there is only 1 restart data stream

i01 -- Data goes into real and into WRF

i1 -- Data goes into real only

Rconfig Entry

| # | Type | Sym | How set | Nentries | Default |
|----------------------|----------------------|-----------------------------|------------------------------------|----------|---------|
| <code>rconfig</code> | <code>integer</code> | <code>spec_bdy_width</code> | <code>namelist, bdy_control</code> | 1 | 1 |

- This defines namelist entries
- Elements
 - *Entry*: the keyword “rconfig”
 - *Type*: the type of the namelist variable (integer, real, logical, string)
 - *Sym*: the name of the namelist variable or array
 - *How set*: indicates how the variable is set: e.g. namelist or derived, and if namelist, which block of the namelist it is set in

Rconfig Entry

| # | Type | Sym | How set | Nentries | Default |
|---------|---------|----------------|-----------------------|----------|---------|
| rconfig | integer | spec_bdy_width | namelist, bdy_control | 1 | 1 |

- This defines namelist entries
- Elements
 - *Nentries*: specifies the dimensionality of the namelist variable or array. If 1 (one) it is a variable and applies to all domains; otherwise specify max_domains (which is an integer parameter defined in module_driver_constants.F).
 - *Default*: the default value of the variable to be used if none is specified in the namelist; hyphen (-) for no default

Rconfig Entry

| # | Type | Sym | How set | Nentries | Default |
|---------|---------|----------------|-----------------------|----------|---------|
| rconfig | integer | spec_bdy_width | namelist, bdy_control | 1 | 1 |

- Result of this Registry Entry:
 - Define an namelist variable “spec_bdy_width” in the bdy_control section of namelist.input
 - Type integer (others: real, logical, character)
 - If this is first entry in that section, define “bdy_control” as a new section in the namelist.input file
 - Specifies that bdy_control applies to all domains in the run as number of entries = 1

```
--- File: namelist.input ---  
  
&bdy_control  
  spec_bdy_width      = 5,  
  spec_zone           = 1,  
  relax_zone          = 4,  
  . . .  
/
```

Rconfig Entry

| # | Type | Sym | How set | Nentries | Default |
|---------|---------|----------------|-----------------------|----------|---------|
| rconfig | integer | spec_bdy_width | namelist, bdy_control | 1 | 1 |

- Result of this Registry Entry:
 - if **Nentries** is “**max_domains**” then the entry in the namelist.input file is a comma-separated list, each element of which applies to a separate domain
 - The single entry in the Registry file applies to each of the separate domains

```
--- File: namelist.input ---  
  
&bdy_control  
  spec_bdy_width      = 5,  
  spec_zone           = 1,  
  relax_zone          = 4,  
  . . .  
/
```

Rconfig Entry

| # | Type | Sym | How set | Nentries | Default |
|---------|---------|----------------|-----------------------|----------|---------|
| rconfig | integer | spec_bdy_width | namelist, bdy_control | 1 | 1 |

- Result of this Registry Entry:
 - Specify a **default** value of “1” if nothing is specified in the namelist.input file
 - In the case of a multi-process run, generate code to read in the bdy_control section of the namelist.input file on one process and broadcast the value to all other processes

```
--- File: namelist.input ---  
  
&bdy_control  
  spec_bdy_width      = 5,  
  spec_zone           = 1,  
  relax_zone          = 4,  
  . . .  
/
```

Package Entry

- Elements
 - *Entry*: the keyword “package”,
 - *Package name*: the name of the package: e.g. “kesslerscheme”
 - *Associated rconfig choice*: the name of a rconfig variable and the value of that variable that chooses this package

```
# specification of microphysics options
package    passiveqv      mp_physics==0      -      moist:qv
package    kesslerscheme  mp_physics==1      -      moist:qv,qc,qr
package    linscheme      mp_physics==2      -      moist:qv,qc,qr,qi,qs,qg
package    ncepcloud3     mp_physics==3      -      moist:qv,qc,qr
package    ncepcloud5     mp_physics==4      -      moist:qv,qc,qr,qi,qs

# namelist entry that controls microphysics option
rconfig    integer      mp_physics    namelist,physics    max_domains    0
```

Package Entry

- Elements
 - *Package state vars*: unused at present; must specify hyphen (-)
 - *Associated variables*: the names of 4D scalar arrays ([moist](#), [chem](#), [scalar](#), [tracer](#)) and the fields within those arrays this package uses, and the state variables ([state:u_gc](#), ...)

```
# specification of microphysics options
package    passiveqv      mp_physics==0      -      moist:qv
package    kesslercheme  mp_physics==1      -      moist:qv,qc,qc
package    linscheme      mp_physics==2      -      moist:qv,qc,qc,qi,qs,qg
package    ncepcloud3     mp_physics==3      -      moist:qv,qc,qc
package    ncepcloud5     mp_physics==4      -      moist:qv,qc,qc,qi,qs

# namelist entry that controls microphysics option
rconfig    integer        mp_physics    namelist,physics    max_domains    0
```

Package Entry

```
USE module_state_descriptions

...

Micro_select : SELECT CASE ( mp_physics )

    CASE ( KESSLERScheme )
        CALL kessler ( ...

    CASE ( THOMPSON )
        CALL mp_gt_driver ( ...

    ...

END SELECT micro_select
```

Packages define automatically enumerated types to avoid the usual tests (i.e. option #17 for microphysics)

Halo Entry

- Elements
 - *Entry*: the keyword “halo”,
 - *Communication name*: given to the particular communication, must be identical in the source code (case matters!)
 - *Associated dynamical core*: dyn_em XOR dyn_nmm are acceptable
 - *Stencil size*: 4, or $(2n+1)^2-1$ (i.e. 8, 24, 48; semi-colon separated)
 - *Which variables*: names of the variables (comma separated)

```
# Halo update communications
halo      HALO_EM_TKE_C dyn_em 4:ph_2,phb
```

HALO Entry

Place communication in dyn_em/solve_em.F

```
#ifndef DM_PARALLEL
#    include "HALO_EM_TKE_C.inc"
#endif
```

```
# Halo update communications
halo      HALO_EM_TKE_C dyn_em 4:ph_2,phb
```

PERIOD and XPOSE Entry

- Elements
 - *Entry*: the keyword “period” or “xpose” (transpose)
 - *Communication name*: given to the particular communication, must be identical in the source code (case matters!)
 - *Associated dynamical core*: dyn_em XOR dyn_nmm are acceptable
 - *Stencil size for period*: # rows and columns to share for periodic lateral BCs
 - *Which variables for period*: names of the variables (comma separated)
 - *Which variables for xpose*: original variable (3d), x-transposed and y-transposed fields

```
# Period update communications
period PERIOD_EM_COUPLE_A dyn_em 2:mub,mu_1,mu_2
```

```
# Transpose update communications
xpose XPOSE_POLAR_FILTER_TOPO dyn_em t_init,t_xxx,dum_yyy
```

Registry IO: registry.io_boilerplate

- **include** — method to populate Registry without duplicating information which is prone to error
 - *Entry*: the keyword “include”
 - *Name*: file name to include in the Registry file

| Entry | Name |
|----------------------|--------------------------------------|
| <code>include</code> | <code>registry.io_boilerplate</code> |

Registry IO: registry.io_boilerplate

- **rconfig** - namelist entries
 - *Entry*: the keyword “rconfig”,
 - *Type*: integer, logical, real
 - *Symbol*: name of variable in namelist
 - *How set*: name of the resident record (*usually*)
 - *Number of entries*: either “1” or “max_domains”
 - *Default value*: what to define if not in namelist.input file
 - *NOT REQUIRED name and description*: for self documentation purposes

| Entry | Type | Sym | How set |
|---------|-----------|------------------|-----------------------|
| rconfig | character | auxinput5_inname | namelist,time_control |

| Num Entries | Default |
|-------------|------------------------------|
| 1 | "auxinput5_d<domain>_<date>" |

<domain> expanded to 2-digit domain identifier

<date> expanded to the usual WRF “years down to seconds” date string

Registry IO: possible values for this single stream

| Entry | Type | Sym | How set |
|---------|-----------|-----------------------|-----------------------|
| rconfig | character | auxinput5_outname | namelist,time_control |
| rconfig | character | auxinput5_inname | namelist,time_control |
| rconfig | integer | auxinput5_interval_mo | namelist,time_control |
| rconfig | integer | auxinput5_interval_d | namelist,time_control |
| rconfig | integer | auxinput5_interval_h | namelist,time_control |
| rconfig | integer | auxinput5_interval_m | namelist,time_control |
| rconfig | integer | auxinput5_interval_s | namelist,time_control |
| rconfig | integer | auxinput5_interval | namelist,time_control |
| rconfig | integer | auxinput5_begin_y | namelist,time_control |
| rconfig | integer | auxinput5_begin_mo | namelist,time_control |
| rconfig | integer | auxinput5_begin_d | namelist,time_control |
| rconfig | integer | auxinput5_begin_h | namelist,time_control |
| rconfig | integer | auxinput5_begin_m | namelist,time_control |
| rconfig | integer | auxinput5_begin_s | namelist,time_control |
| rconfig | integer | auxinput5_end_y | namelist,time_control |
| rconfig | integer | auxinput5_end_mo | namelist,time_control |
| rconfig | integer | auxinput5_end_d | namelist,time_control |
| rconfig | integer | auxinput5_end_h | namelist,time_control |
| rconfig | integer | auxinput5_end_m | namelist,time_control |
| rconfig | integer | auxinput5_end_s | namelist,time_control |
| rconfig | integer | io_form_auxinput5 | namelist,time_control |

Registry IO: different available input streams

| Entry | Type | Sym | How set |
|---------|---------|--------------------|-----------------------|
| rconfig | integer | io_form_input | namelist,time_control |
| rconfig | integer | io_form_history | namelist,time_control |
| rconfig | integer | io_form_restart | namelist,time_control |
| rconfig | integer | io_form_boundary | namelist,time_control |
| | | | |
| rconfig | integer | io_form_auxinput1 | namelist,time_control |
| rconfig | integer | io_form_auxinput2 | namelist,time_control |
| rconfig | integer | io_form_auxinput3 | namelist,time_control |
| rconfig | integer | io_form_auxinput4 | namelist,time_control |
| rconfig | integer | io_form_auxinput5 | namelist,time_control |
| rconfig | integer | io_form_auxinput6 | namelist,time_control |
| rconfig | integer | io_form_auxinput7 | namelist,time_control |
| rconfig | integer | io_form_auxinput8 | namelist,time_control |
| through | | | |
| rconfig | integer | io_form_auxinput24 | namelist,time_control |
| | | | |
| rconfig | integer | io_form_gfdda | namelist,fd |
| rconfig | integer | io_form_auxinput11 | namelist,time_control |

For any given WRF model fcst, users have access to these input streams

Registry IO: registry.io_boilerplate

| Entry | Type | Sym | How set |
|---------|---------|-------------------|-----------------------|
| rconfig | integer | io_form_auxhist1 | namelist,time_control |
| rconfig | integer | io_form_auxhist2 | namelist,time_control |
| rconfig | integer | io_form_auxhist3 | namelist,time_control |
| rconfig | integer | io_form_auxhist4 | namelist,time_control |
| rconfig | integer | io_form_auxhist5 | namelist,time_control |
| rconfig | integer | io_form_auxhist6 | namelist,time_control |
| rconfig | integer | io_form_auxhist7 | namelist,time_control |
| rconfig | integer | io_form_auxhist8 | namelist,time_control |
| rconfig | integer | io_form_auxhist9 | namelist,time_control |
| rconfig | integer | io_form_auxhist10 | namelist,time_control |
| rconfig | integer | io_form_auxhist11 | namelist,time_control |
| through | | | |
| rconfig | integer | io_form_auxhist24 | namelist,time_control |

... and
access to
these
output
streams

Registry Data Base - Review

- Currently implemented as a text file: *Registry/Registry.EM*
- Types of entry:
 - *Dimspec*— dimensions that are used to define arrays in the model
 - *State*— variables and arrays in the domain structure
 - */1*— local variables and arrays in solve, typically tendency values
 - *Typedef*— derived types that are subtypes of the domain structure

Registry Data Base - Review

- Types of entry:
 - *Rconfig* — configuration (e.g. namelist) variable or array
 - *Package* — attributes of a package (e.g. physics)
 - *Halo* — interprocessor communications
 - *Period* — communications for periodic boundary updates
 - *Xpose* — communications for parallel matrix transposes
 - *Include* — similar to a CPP `#include` file

Outline

- Registry Mechanics

- Examples

- 0) Add output without recompiling
- 1) Add a variable to the namelist
- 2) Add an array
- 3) Compute a diagnostic
- 4) Add a physics package

Example 0: Add output without recompiling

- Edit the namelist.input file, the time_control namelist record

```
iofields_filename = "myoutfields.txt"
```

```
io_form_auxhist7 = 2 (choose an available stream)
```

```
auxhist7_interval = 10 (every 10 minutes)
```

- Place the fields that you want in the named text file **myoutfields.txt**

```
+ :h:7:RAIN,RAINNC
```

- Where “+” means ADD this variable to the output stream, “h” is the history stream, and “7” is the stream number
- **iofields_filename** is MAX_DOMAIN dimensioned

Example 0: Add output without recompiling

- Edit the namelist.input file, the time_control namelist record

```
iofields_filename = "myoutfields.txt"
```

- Place the fields that you want in the named text file **myoutfields.txt**

```
- : h : 0 : W, PB, P
```

- Where “-” means REMOVE this variable from the output stream, “h” is the history stream, and “0” is the stream number (standard WRF history file)

Example 1: Add a variable to the namelist

- Use the examples for the **rconfig** section of the Registry
- Find a namelist variable similar to what you want
 - Integer *vs* real *vs* logical *vs* character
 - Single value *vs* value per domain
 - Select appropriate namelist record
- Insert your mods in all appropriate Registry files
- Remember that ALL Registry changes require that the WRF code be cleaned and rebuilt

```
./clean -a  
./configure  
./compile em_real
```

Example 1: Add a variable to the namelist

- Adding a variable to the namelist requires the inclusion of a new line in the Registry file:

```
rconfig integer my_option_1 namelist,time_control 1 0 - "my_option_1" "test namelist option"  
rconfig integer my_option_2 namelist,time_control max_domains 0
```

- Accessing the variable is through an automatically generated function:

```
USE module_configure  
INTEGER :: my_option_1 , my_option_2  
  
CALL nl_get_my_option_1( 1, my_option_1 )  
CALL nl_set_my_option_2( grid%id, my_option_2 )
```

Example 1: Add a variable to the namelist

- You also have access to the namelist variables from the grid structure ...

```
SUBROUTINE foo ( grid , ... )
```

```
USE module_domain
```

```
TYPE(domain) :: grid
```

```
print *,grid%my_option_1
```

```
print *,grid%my_option_2
```


Example 1: Add a variable to the namelist

- ... and you also have access to the namelist variables from config_flags

```
SUBROUTINE foo2 ( config_flags , ... )  
  
  USE module_configure  
  TYPE(grid_config_rec_type) :: config_flags  
  
  print *,config_flags%my_option_1  
  print *,config_flags%my_option_2
```

Example 1: Add a variable to the namelist

- What your variable looks like in the namelist.input file

```
&time_control  
run_days           = 0,  
run_hours          = 0,  
run_minutes        = 40,  
run_seconds        = 0,  
start_year         = 2006, 2006, 2006,  
my_option_1        = 17  
my_option_2        = 1, 2, 3
```

Examples

- 1) Add a variable to the namelist
- 2) Add an array to solver, and IO stream
- 3) Compute a diagnostic
- 4) Add a physics package

Example 2: Add an Array

- Adding an array to the solver, requires adding a **single line** in the Registry
- Use the previous Registry instructions for either a **state** or **I1** variable
- Select a variable **similar** to one that you would like to add
 - 1d, 2d, or 3d
 - Staggered (X, Y, Z, or not “-”, *do not leave blank*)
 - Associated with a package
 - Part of a 4d array
 - Input (012), output, restart
 - Nesting, lateral forcing, feedback
 - Masked

Example 2: Add an Array

- Copy the “similar” field’s line and make a few edits
- Remember, no Registry change takes effect until a “clean -a” and rebuild
- Always modify Registry.*core_name*, where *core_name* might be EM for example

```
state  real  h_diabatic  ij  misc  1  -      r      \
      "h_diabatic"    "PREVIOUS TIMESTEP CONDENSATIONAL HEATING"

state  real  msft      ij  misc  1  -      i012rhdu=(copy_fcnm) \
      "MAPFAC_M"      "Map scale factor on mass grid"

state  real  ht      ij  misc  1  -      i012rhdu      \
      "HGT"          "Terrain Height"

state  real  ht_input  ij  misc  1  -      -      \
      "HGT_INPUT"    "Terrain Height from FG Input File"

state  real  TSK_SAVE  ij  misc  1  -      -      \
      "TSK_SAVE"     "SURFACE SKIN TEMPERATURE"  "K"
```

Examples

- 1) Add a variable to the namelist
- 2) Add an array
- 3) Compute a diagnostic
- 4) Add a physics package

Example 3: Compute a Diagnostic

- Problem: Output global average and global maximum and lat/lon location of maximum for 10 meter wind speed in WRF
- Steps:
 - Modify solve to compute wind-speed and then compute the local sum and maxima at the end of each time step
 - Use reduction operations built-in to WRF software to compute the global qualities
 - Output these on one process (process zero, the “monitor” process)

Example 3: Compute a Diagnostic

- Compute local sum and local max and the local indices of the local maximum

```
--- File: dyn_em/solve_em.F (near the end) ---  
  
! Compute local maximum and sum of 10m wind-speed  
sum_ws = 0.  
max_ws = 0.  
DO j = jps, jpe  
  DO i = ips, ipe  
    wind_vel = sqrt( grid%u10(i,j)**2+ grid%v10(i,j)**2 )  
    IF ( wind_vel .GT. max_ws ) THEN  
      max_ws = wind_vel  
      idex = i  
      jdex = j  
    ENDIF  
    sum_ws = sum_ws + wind_vel  
  ENDDO  
ENDDO
```


Example 3: Compute a Diagnostic

- Compute global sum, global max, and indices of the global max (WRF intrinsics)

```
! Compute global sum
  sum_ws = wrf_dm_sum_real ( sum_ws )

! Compute global maximum and associated i,j point
  CALL wrf_dm_maxval_real ( max_ws, idex, jdex )
```

Example 3: Compute a Diagnostic

- On the process that contains the maximum value, obtain the latitude and longitude of that point; on other processes set to an artificially low value.
- The use parallel reduction to store that result on every process

```
IF ( ips .LE. idex .AND. idex .LE. ipe .AND. &  
    jps .LE. jdex .AND. jdex .LE. jpe ) THEN  
    glat = grid%xlatt(idex,jdex)  
    glon = grid%xlong(idex,jdex)  
ELSE  
    glat = -99999.  
    glon = -99999.  
ENDIF
```

```
! Compute global maximum to find glat and glon  
glat = wrf_dm_max_real ( glat )  
glon = wrf_dm_max_real ( glon )
```

Example 3: Compute a Diagnostic

- Output the value on process zero, the “monitor”

```
! Print out the result on the monitor process
  IF ( wrf_dm_on_monitor() ) THEN
    WRITE(outstring,*) 'Avg. ',sum_ws/((ide-ids+1)*(jde-jds+1))
    CALL wrf_message ( TRIM(outstring) )
    WRITE(outstring,*) 'Max. ',max_ws,' Lat. ',glat,&
                                ' Lon. ',glon
    CALL wrf_message ( TRIM(outstring) )
  ENDIF
```

Example 3: Compute a Diagnostic

- Output from process zero of an n process run

```
--- Output file: rsl.out.0000 ---  
. . .  
Avg.      5.159380  
Max.      15.09370    Lat.      37.25022    Lon.     -67.44571  
Timing for main: time 2000-01-24_12:03:00 on domain  1:      8.96500 elapsed secs.  
Avg.      5.166167  
Max.      14.97418    Lat.      37.25022    Lon.     -67.44571  
Timing for main: time 2000-01-24_12:06:00 on domain  1:      4.89460 elapsed secs.  
Avg.      5.205693  
Max.      14.92687    Lat.      37.25022    Lon.     -67.44571  
Timing for main: time 2000-01-24_12:09:00 on domain  1:      4.83500 elapsed secs.  
. . .
```

Examples

- 1) Add a variable to the namelist
- 2) Add an array
- 3) Compute a diagnostic
- 4) Add a physics package

Example 4: Input periodic SSTs

- Add a new physics package with time varying input source to the model
- This is how we could supply a time varying value to the model for a field that is traditionally fixed
- Example is sea surface temperature (over engineered solution for how we currently implement the SST_UPDATE option)

Example 4: Input periodic SSTs

- Problem: adapt WRF to input a time-varying lower boundary condition, e.g. SSTs, from an input file for a new surface scheme
- Given: Input file in WRF I/O format containing 12-hourly SST's
- Modify WRF model to read these into a new state array and make available to WRF surface physics

Example 4: Input periodic SSTs

- Steps
 - Add a new state variable and definition of a new surface layer package (that will use the variable) to the Registry
 - Add to variable stream for an unused Auxiliary Input stream
 - Adapt physics interface to pass new state variable to physics
 - Setup namelist to input the file at desired interval

Example 4: Input periodic SSTs

- Add a new state variable to Registry/Registry.EM or Registry/Registry.NMM and put it in the variable set for input on AuxInput #4

| # | type | symbol | dims | use | tl | stag | io | dname | description | units |
|-------|------|--------|------|------|----|------|------|-----------|--------------------|-------|
| state | real | nsst | ij | misc | 1 | - | i4rh | "NEW_SST" | "Time Varying SST" | "K" |

- Also added to History and Restart
- Result:
 - 2-D variable named **nsst** defined and available in solve_em
 - Dimensions: ims:ime, jms:jme
 - Input and output on the AuxInput #4 stream will include the variable under the name NEW_SST

Example 4: Input periodic SSTs

- Pass new state variable to surface physics

```
--- File: dyn_em/module_first_rk_step_part1.F ---

CALL surface_driver(                                     &
    . . .
! Optional
&      ,QV_CURR=moist(ims,kms,jms,P_QV) , F_QV=F_QV      &
&      ,QC_CURR=moist(ims,kms,jms,P_QC) , F_QC=F_QC      &
&      ,QR_CURR=moist(ims,kms,jms,P_QR) , F_QR=F_QR      &
&      ,QI_CURR=moist(ims,kms,jms,P_QI) , F_QI=F_QI      &
&      ,QS_CURR=moist(ims,kms,jms,P_QS) , F_QS=F_QS      &
&      ,QG_CURR=moist(ims,kms,jms,P_QG) , F_QG=F_QG      &
&      ,NSST=grid%nsst                                     & ! new
&      ,CAPG=grid%capg, EMISS=grid%emiss, HOL=hol,MOL=grid%mol &
&      ,RAINBL=grid%rainbl,SR=grid%em_sr                  &
&      ,RAINNCV=grid%rainncv,REGIME=regime,T2=grid%t2,THC=grid%thc &
    . . .
```

Example 4: Input periodic SSTs

- Add new variable `nsst` to Physics Driver in Mediation Layer

```
--- File: phys/module_surface_driver.F ---

SUBROUTINE surface_driver(                                &
    . . .
    ! Other optionals (more or less em specific)
    &      ,nsst                                          &
    &      ,capg,emiss,hol,mol                            &
    &      ,rainncv,rainbl,regime,t2,thc                  &
    &      ,qsg,qvg,qcg,soilt1,tsnav                     &
    &      ,smfr3d,keepfr3dflag                           &
    . . .
                                                    ))

    . . .
REAL, DIMENSION( ims:ime, jms:jme ), OPTIONAL, INTENT(INOUT):: nsst
```

- By making this an “Optional” argument, we preserve the driver’s compatibility with other cores and with versions of WRF where this variable hasn’t been added.

Example 4: Input periodic SSTs

- Add call to Model-Layer subroutine for new physics package to Surface Driver

```
--- File: phys/module_surface_driver ---

!$OMP PARALLEL DO  &
!$OMP PRIVATE ( ij, i, j, k )
DO ij = 1 , num_tiles
  sfclay_select: SELECT CASE(sf_sfclay_physics)

    CASE (SFCLAYScheme)
      . . .
    CASE (NEWSFCSCHEME) ! <- This is defined by the Registry "package" entry

      IF (PRESENT(nsst)) THEN
        CALL NEWSFCSCHEME(
          nsst,
          ids,ide, jds,jde, kds,kde,
          ims,ime, jms,jme, kms,kme,
          i_start(ij),i_end(ij), j_start(ij),j_end(ij), kts,kte
        )
      ELSE
        CALL wrf_error_fatal('Missing argument for NEWScheme in surface driver')
      ENDIF
    . . .
  END SELECT sfclay_select
ENDDO
!$OMP END PARALLEL DO
```

- Note the PRESENT test to make sure new optional variable nsst is available

Example 4: Input periodic SSTs

- Add definition for new physics package NEWScheme as setting 4 for namelist variable `sf_sfclay_physics`

| | | | | | |
|----------------------|---------------------------|-----------------------------------|-------------------------------|--------------------------|----------------|
| <code>rconfig</code> | <code>integer</code> | <code>sf_sfclay_physics</code> | <code>namelist,physics</code> | <code>max_domains</code> | <code>0</code> |
| <code>package</code> | <code>sfclayscheme</code> | <code>sf_sfclay_physics==1</code> | - | - | |
| <code>package</code> | <code>myjsfcscheme</code> | <code>sf_sfclay_physics==2</code> | - | - | |
| <code>package</code> | <code>gfssfcscheme</code> | <code>sf_sfclay_physics==3</code> | - | - | |
| <code>package</code> | <code>newsfcscheme</code> | <code>sf_sfclay_physics==4</code> | - | - | |

- This creates a defined constant NEWSFCScheme and represents selection of the new scheme when the namelist variable `sf_sfclay_physics` is set to '4' in the `namelist.input` file
- **clean -a** and recompile so code and Registry changes take effect

Example 4: Input periodic SSTs

- Setup namelist to input SSTs from the file at desired interval

```
      --- File: namelist.input ---  
  
&time_control  
  . . .  
  auxinput4_inname      = "sst_input"  
  auxinput4_interval_h  = 12  
  . . .  
/  
  
  . . .  
&physics  
  sf_sfclay_physics    = 4, 4, 4  
  . . .  
/
```

- Run code with sst_input file in run-directory

Example 4: Input periodic SSTs

- A few notes...
 - The read times and the time-stamps in the input file must match exactly
 - We haven't done anything about what happens if the file runs out of time periods (the last time period read will be used over and over again, though you'll see some error messages in the output if you set `debug_level` to be 1 or greater in `namelist.input`)
 - We haven't said anything about what generates `sst_input`

(as close as possible, Klingon for *finis*)



Hegh!