


Post-processing Tools: NCL



Abby Jaye


NCL

- NCAR Command Language
- Website: <http://www.ncl.ucar.edu>
- Reads WRF-ARW data directly
- Can generate many types of graphical plots
 - Horizontal
 - Cross-section
 - SkewT
 - Meteogram
 - Panel


2

Example Plots


Soil Temperature




LU-INDEX




Total Precipitation




Terrain Height



Relative Humidity
Vertical X-section




Sfc Temperature
Horizontal X-section




3


Example Plots




Skew-T Diagram




Domain Overlay



Time Series




Wind Rose




4

Example Plots




Example Plot Functions



Generating Plots

A good start: WRF Online Tutorial

<http://www2.mmm.ucar.edu/wrf/OnLineTutorial/Graphics/NCL/index.html>




NCL Download

<http://www.ncl.ucar.edu/Download>

- Fill out short registration form (short waiting period)
- Read and agree to OSI-based license
- Get version 6 or LATER (current: v6.3.0)

****Always download binary code instead of source code****

NCL & WRF



9

~/hluresfile


- Very important for NCL versions earlier than v6
 - <http://www.ncl.ucar.edu/Document/Graphics/hlures.shtml>
- Must be placed in your “~/” directory (*home directory*)
- Will control:
 - Color table; font
 - White/black background
 - Size of plot
 - Characters

10

~/hluresfile


Without it:

```
PLCHHQ - CHARACTER NUMBER 26 (.) IS NOT A LEGAL FUNCTION CODE
PLCHHQ - CHARACTER NUMBER 29 (t) IS NOT A LEGAL FUNCTION CODE
PLCHHQ - CHARACTER NUMBER 30 (o) IS NOT A LEGAL FUNCTION CODE
PLCHHQ - CHARACTER NUMBER 32 (.) IS NOT A LEGAL FUNCTION CODE
PLCHHQ - CHARACTER NUMBER 35 (b) IS NOT A LEGAL FUNCTION CODE
PLCHHQ - CHARACTER NUMBER 36 (y) IS NOT A LEGAL FUNCTION CODE
```



With it:

```
*wkColorMap      : ncl_default
*wkBackgroundColor : white
*wkForegroundColor : black
*FuncCode        : ~
*TextFuncCode     : ~
*Font            : helvetica
*wkWidth         : 1000
*wkHeight        : 1000
```



11

Generating Plots

- Set NCARG_ROOT environment variable
 - `setenv NCARG_ROOT /usr/local/ncl` ← for example
- Ensure you have a `~/hluresfile` file
- Create a script
 - `wrf_real.ncl`
 - (start with a sample script)
 - Most of the WRF script routines are called from `"$NCARG_ROOT/lib/ncarg/nclscripts/wrf/WRFUserARW.ncl"`
 - Feel free to add or change this script
- Run NCL script
 - `ncl wrf_real.ncl`

12

Creating a Plot: NCL script

```
load ncl library scripts

begin

; Open input file(s)
; Open graphical output

; Read variables

; Set up plot resources & Create plots
; Output graphics

end
```

13

Creating a Plot: NCL script

```
load "$NCARG_ROOT/lib/ncarg/nclscripts/csm/gsn_code.ncl"
load "$NCARG_ROOT/lib/ncarg/nclscripts/wrf/WRFUserARW.ncl"

begin

; Open input file(s)
; Open graphical output

; Read variables

; Set up plot resources & Create plots
; Output graphics

end
```

Load not required for NCL version 6.3
load "/mydir/myWRFUserARW.ncl"

14

Creating a Plot: NCL script

```
load "$NCARG_ROOT/lib/ncarg/nclscripts/csm/gsn_code.ncl"
load "$NCARG_ROOT/lib/ncarg/nclscripts/wrf/WRFUserARW.ncl"

begin

; Open input file(s)
; Open graphical output

; Read variables

; Set up plot resources & Create plots
; Output graphics

end
```

15

Creating a Plot: NCL script

```
load "$NCARG_ROOT/lib/ncarg/nclscripts/csm/gsn_code.ncl"
load "$NCARG_ROOT/lib/ncarg/nclscripts/wrf/WRFUserARW.ncl"

begin

a = addfile("./wrfout_d01_2012-09-28_00:00:00.nc", "r")
; Open graphical output

; Read variables

; Set up plot resources & Create plots
; Output graphics

end
```

a = addfile("./
wrfout_d01_2005-10-08_00:00:00.nc", "r")
Can be "r", "w", "c"

```
> ls wrfout*
wrfout_d01_2005-10-08_00:00:00

a = addfile("./
wrfout_d01_2005-10-08_00:00:00.nc", "r")
```

16

Creating a Plot: NCL script

```
load "$NCARG_ROOT/lib/ncarg/nclscripts/csm/gsn_code.ncl"
load "$NCARG_ROOT/lib/ncarg/nclscripts/wrf/WRFUserARW.ncl"
```

```
begin
```

```
  a = addfile("./wrfout_d01_2012-09-28_00:00:00.nc","r")
  wks = gsn_open_wks("X11","plt_Surface")
```

```
  ; Read variables
```

```
  ; Set up plot resources & Create plots
  ; Output graphics
```

```
end
```

Can output either on the screen (X11),
or as pdf, ps, png, cgm

17

Creating a Plot: NCL script

```
load "$NCARG_ROOT/lib/ncarg/nclscripts/csm/gsn_code.ncl"
load "$NCARG_ROOT/lib/ncarg/nclscripts/wrf/WRFUserARW.ncl"
```

```
begin
```

```
  a = addfile("./wrfout_d01_2012-09-28_00:00:00.nc","r")
  wks = gsn_open_wks("X11","plt_Surface")
```

```
  T2 = wrf_user_getvar(a,"T2",0)
```

```
  ; Set up plot resources & Create plots
  ; Output graphics
```

```
end
```

```
T2 = wrf_user_getvar(a,"T2",0)
T2 = a->T2(0,,:)
```

```
T2 = wrf_user_getvar(a,"T2",-1)
T2 = a->T2
```

18

Special WRF NCL Functions

wrf_user_getvar

Get fields from input file

```
ter = wrf_user_getvar(a,"HGT",0)      {ter=a->HGT(0,,:)}
t2 = wrf_user_getvar(a,"T2",-1)       {t2=a->T2}
slp = wrf_user_getvar(a,"slp",1)
```

avo/pvo: Absolute/Potential Vorticity, **eth**: Equivalent Potential Temperature,
cape_2d: 2D mcape/mcin/lcl/lfc, **cape_3d**: 3D cape/cin,
ctt: cloud top temperature, **dbz/mbdz**: Reflectivity (3D and max),
geopt/geopotential: Geopotential, **lat/ion**: latitude/longitude
helicity/updraft_helicity: Storm Relative Helicity/Updraft helicity,
omg: Omega, **p/pres/pressure**: Pressure, **pw**: Precipitable Water,
rh/rh2: Relative Humidity (3D and 2m),
slp: Sea Level Pressure, **times**: Time as a string [(Times: Time as characters)],
td/td2: Dew Point Temperature (3D and 2m), **ter**: terrain,
tc/tk: Temperature (C and F), **th/theta**: Potential Temperature,
tv: Virtual Temperature, **twb**: Wetbulb Temperature,
z/height: Height, **ua/va/wa**: wind on mass points,
uvmet/uvmet10: wind rotated to earth coordinates (3D and 10m)

19

Creating a Plot: NCL script

```
load "$NCARG_ROOT/lib/ncarg/nclscripts/csm/gsn_code.ncl"
load "$NCARG_ROOT/lib/ncarg/nclscripts/wrf/WRFUserARW.ncl"
```

```
begin
```

```
  a = addfile("./wrfout_d01_2012-09-28_00:00:00.nc","r")
  wks = gsn_open_wks("X11","plt_Surface")
```

```
  T2 = wrf_user_getvar(a,"T2",0)
```

```
  ; Set up plot resources & Create plots
  ; Output graphics
```

```
end
```

20

Creating a Plot: NCL script

```
load "$NCARG_ROOT/lib/ncarg/nclscripts/csm/gsn_code.ncl"
load "$NCARG_ROOT/lib/ncarg/nclscripts/wrf/WRFUserARW.ncl"

begin

  a = addfile("./wrfout_d01_2012-09-28_00:00:00.nc","r")
  wks = gsn_open_wks("X11","plt_Surface")

  T2 = wrf_user_getvar(a,"T2",0)

  pltres = True
  mpres = True
  opts = True
  opts@cnFillOn = True
  ; Output graphics

end
```

pltres: Plotting resources - like overlays
mpres: Map resources - like map resolution
and zooming option

opts: Resources associated with each
individual plot

21

Creating a Plot: NCL script

```
load "$NCARG_ROOT/lib/ncarg/nclscripts/csm/gsn_code.ncl"
load "$NCARG_ROOT/lib/ncarg/nclscripts/wrf/WRFUserARW.ncl"

begin

  a = addfile("./wrfout_d01_2012-09-28_00:00:00.nc","r")
  wks = gsn_open_wks("X11","plt_Surface")

  T2 = wrf_user_getvar(a,"T2",0)

  pltres = True
  mpres = True
  opts = True
  opts@cnFillOn = True
  contour_t2 = wrf_contour(a,wks,T2,opts)
  plot= wrf_map_overlays(a,wks, (/contour_t2/),pltres,mpres)

end
```

22

Creating

```
load "$NCARG_ROOT/lib/ncarg/nclscripts/csm/gsn_code.ncl"
load "$NCARG_ROOT/lib/ncarg/nclscripts/wrf/WRFUserARW.ncl"


begin

  a = addfile("./wrfout_d01_2012-09-28_00:00:00.nc","r")
  wks = gsn_open_wks("X11","plt_Surface")

  T2 = wrf_user_getvar(a,"T2",0)

  pltres = True
  mpres = True
  opts = True
  opts@cnFillOn = True
  contour_t2 = wrf_contour(a,wks,T2,opts)
  plot= wrf_map_overlays(a,wks, (/contour_t2/),pltres,mpres)

end
```



23

Creating a Plot: NCL script

```
T2 = wrf_user_getvar(a,"T2",0)
slp = wrf_user_getvar(a,"slp",0)

pltres = True
mpres = True

opts = True
opts@cnFillOn = True
contour_t2 = wrf_contour(a,wks,T2,opts)
delete(opts)

opts = True
opts@cnLineColor = "Blue"
contour_slp = wrf_contour(a,wks,slp,opts)
delete(opts)

plot = wrf_map_overlays(a,wks, (/contour_t2,contour_slp/),
  pltres,mpres)

end
```

24

Creating a

```
T2 = wrf_user_getvar(a,"
slp = wrf_user_getvar(a,


pltres = True
mpres = True

opts = True
opts@cnFillOn = True
contour t2 = wrf_contour
delete(opts)

opts = True
opts@cnLineColor = "Blue
contour slp = wrf_contou
delete(opts)

plot = wrf_map_overlays(a,wks,(/contour_t2,contour_slp/),
pltres,mpres)
```


end



25

Special WRF NCL Functions

- `wrf_user_getvar`
Get native and diagnostic variables
- `wrf_contour` / `wrf_vector`
Create line/shaded & vector plots
- `wrf_map_overlays` / `wrf_overlays`
Overlay plots created with `wrf_contour` and `wrf_vector`
- `wrf_user_intrp3d` / `wrf_user_intrp2d`
*Interpolate horizontally to a given pressure/height
(3d data only)
Interpolate vertically along a given line*
- `wrf_user_ll_to_ij` / `wrf_user_ij_to_ll`
Convert: lat/lon ↔ ij
- `wrf_user_unstagger`
Unstagger an array
- `wrf_user_vert_interp`
- `wrf_wps_read_int` / `wrf_wps_write_int`



26

NCL and WRF_NCL

- Combine strength of WRF_NCL specific and NCL general capabilities

```
plot = wrf_map_overlays \
(a,wks,(/contour/),pltres,mpres)

mpres@mpGridSpacingF = 45
plot = wrf_map_overlays \
(a,wks,(/contour/),pltres,mpres)

mpres@mpGeophysicalLineColor
mpres@mpGridLineColor
mpres@mpNationalLineColor
mpres@mpUSStateLineColor

mpres@mpOutlineBoundarySets
"NoBoundaries" ; "Geophysical"
"National" ; "USStates"
"GeophysicalAndUSStates"
"AllBoundaries"
```

```
a = addfile("./wrfout.d01.nc","r")

t2 = a->T2(5, :, :)
t2 = wrf_user_getvar(a,"T2",5)

qv = a->QVAPOR(5, :, :, :)
qv = wrf_user_getvar(a,"QVAPOR",5)

t2 = a->T2
t2 = wrf_user_getvar(a,"T2",-1)

t2 = wrf_user_getvar(a,"T2",
(/0,10,2/))
t2 = wrf_user_getvar(a,"T2",
(/1,2,3,4,5/))
```

27

NCL Resources


- The special WRF functions have unique resources:
<http://www.ncl.ucar.edu/Document/Functions/wrf.shtml>
- All general NCL resources can also be used to control the plot:
<http://www.ncl.ucar.edu/Document/Graphics/Resources>

am (anotation manager)	sf (scalar field)
app (app)	st (streamline)
ca (coordinate array)	tf (transformation)
cn (contour)	ti (title)
ct (coordinate array table)	tm (tickmark)
dc (data comm)	tr (irregular transformation)
err (error)	tx (text)
gs (graphic style)	vc (vectors)
gsn (gsn high-level interfaces)	vf (vector fields)
lb (label bar)	vp (view port)
lg (legends)	wk (workstation)
mp (maps)	ws (workspace)
pm (plot manager)	xy (xy plots)
pr (primitives)	

28

wrf_user_intrp3d

- rh_plane = wrf_user_intrp3d(rh,z,"v",plane,angle,opts)
 - Interpolate "rh" to "z", which by definition is **Height Above Mean Sea Level**



```
z_AGL = z
dims = dimsizes(z)
do k=0,dims(0)-1
  z_AGL(k,:,:) = z_AGL(k,:,:) - ter(:,:)
end do
```

wrf_user_vert_interp

- Interpolate to:
 - "pressure", "pres" - pressure [hPa]
 - "ght_msl" - grid point height msl [km]
 - "ght_agl" - grid point height agl [km]
 - "theta" - potential temperature [K]
 - "theta-e" - equivalent potential temperature [K]
- Extrapolate below the ground
 - Resource - `opts@extrapolate`

30

wrf_user_vert_interp

```
begin
  a = addfile("wrfout_d01_1991-01-01_00:00:00.nc","r")
  tk = wrf_user_getvar(a,"tk",0) ; Get our variable

  vert_coord = "pressure" ; Set the surface we want to interpolate to and which levels
  interp_levels = (/200,300,500,1000/)

  opts = True ; Set options for the function
  opts@extrapolate = True
  opts@field_type = "t"
  opts@logP = True
  tk_interp = wrf_user_vert_interp(a,tk,vert_coord,interp_levels,opts)

  wks = gsn_open_wks("X11","plot_tk_1000mb") ; open the workstation
  opts2 = True ; Set options for the plot
  opts2@cnFillOn = True
  pltres = True
  mpres = True
  mpres@mpGeophysicalLineColor = "Black"
  ; Make the contour and plot it over a map
  contour = wrf_contour(a,wks,tk_interp(0,3,:,:),opts2) ; Plot at time 0 and level 3
  plot = wrf_map_overlays(a,wks,(/contour/),pltres,mpres)
end
```

31


wrf_user_vert_interp

```
begin
  a = addfile("wrfout_d01_1991-01-01_00:00:00.nc","r")
  tk = wrf_user_getvar(a,"tk",0) ; Get our variable

  vert_coord = "pressure" ; Set the surface we want to interpolate to and which levels
  interp_levels = (/200,300,500,1000/)


  opts = True ; Set options for the function
  opts@extrapolate = True
  opts@field_type = "t"
  opts@logP = True
  tk_interp = wrf_user_vert_interp(a,tk,vert_coord,interp_levels,opts)

  wks = gsn_open_wks("X11","plot_tk_1000mb") ; open the workstation
  opts2 = True ; Set options for the plot
  opts2@cnFillOn = True
  pltres = True
  mpres = True
  mpres@mpGeophysicalLineColor = "Black"
  ; Make the contour and plot it over a map
  contour = wrf_contour(a,wks,tk_interp(0,3,:,:),opts2) ; Plot at time 0 and level 3
  plot = wrf_map_overlays(a,wks,(/contour/),pltres,mpres)
end
```




32

wrf_user_ll_to_ij




33

wrf_user_ll_to_ij




34

wrf_user_ll_to_ij



35

wrf_user_ll_to_ij




36

Time Series

```
locij = wrf_user_ll_to_ij(a, -87., 32.5, llres)
locij = locij - 1
locX = locij(0)
locY = locij(1)

t2_point = a->T2(:,locY,locX)
t2_plot = gsn_csm_xy(wks,taus,t2_point,t2_res)

slp = wrf_user_getvar(a,"slp",-1)
slp_point = slp(:,locY,locX)
slp_plot = gsn_csm_xy(wks,taus,slp_point,t2_res)
```




37

Domain Design


```
mp = wrf_wps_dom (wks, mpres, lnres, txres)
WPS/util/plotgrids.ncl
```

Test Domain




38

Overlay Domains




39

Moving Nests



40

Moving Nests



41

Change Fields in netCDF File

```
begin


  DATADir = "/"
  FILES = systemfunc (" ls -l " + DATADir + "met_em.d01* ")
  numFILES = dimsizes(FILES)

  do i=0,numFILES-1
    a = addfile(FILES(i),"w")
    sst = a->SST ; read the field
    sst = sst + 1 ; change the entire field
    a->SST = sst ; write the field back to the file
  end do


end
```

42

Change Fields in netCDF File



```
a = addfile("./geo_em.d01.nc","w")
var= a->LANDUSE
var(:,63:64,83:84) = 7
var(:,62,84) = 7
a->LANDUSE = var
```



43

Data Manipulation in NCL

```
begin

  out = addfile("t2_dailymax_1993-08-20.nc","c") ; Create new netCDF file
  filedimdef(out,"Time",-1,True) ; Make Time unlimited

  a = addfile("wrfout_d01_1993-08-20_00:00:00.nc","r") ;File has 24 time steps
  fileattdef(out,a) ; Transfer attributes to new file
  t = a->T2-273.15
  landmask = a->LANDMASK(0, :, :)
  lat = a->XLAT(0, :, :)
  lon = a->XLONG(0, :, :)
  times = a->Times(0,0:9)

  tland = mask(t,landmask,1) ; Mask out the ocean

  tmax = dim_max_n(t,0) ; Daily max
  tlandmax = dim_max_n(tland,0) ; Daily max with ocean masked out


  ; Write attributes for the variable
  tlandmaxday!0 = "Time"
  tlandmaxday!1 = "south_north"
  tlandmaxday!2 = "west_east"
  tlandmaxday@units = "C"
  tlandmaxday@coordinates = "XLONG XLAT"
  tlandmaxday@description = "DAILY MAX TEMP at 2 M (masked)"

  ; Write out data
  out->XLAT = lat
  out->XLONG = lon
  out->LANDMASK = landmask
  out->T2MAX = tlandmaxday

end
```

44

Data Manipulation in NCL



45

Reading ASCII Data

```
begin
  fname = "/mydir/ascii.txt"
  foo = asciiread(fname, (/21,6/), "integer")
end
```

/mydir/ascii.txt

1950	13	11	3	8	3
1951	10	8	3	5	2
1952	7	6	3	3	1
1953	14	6	2	4	1
1954	11	8	6	2	1
1955	12	9	3	6	2
1956	8	4	2	2	1
1957	8	3	1	2	2
1958	10	7	2	5	3
1959	11	7	5	2	1
1960	7	4	2	2	2
1961	11	8	1	7	4
1962	5	3	2	1	0
1963	9	7	5	2	1
1964	12	6	0	6	4
1965	5	4	3	1	1
1966	11	7	4	3	1
1967	8	6	5	1	1
1968	8	5	5	0	0
1969	18	12	7	5	1
1970	10	5	3	2	0

Variable: foo
Dimensions and sizes:
[Data|21] x [Columns|6]

(0,0) 1950
(0,1) 13
(0,2) 11
(0,3) 3
(0,4) 8
(0,5) 3
(1,0) 1951
(1,1) 10

46

Reading ASCII Data: Trajectory

begin

```
flnm = "track-1995_0723-0812-380.txt"
n_col = numAsciiCol(flnm)
```

```
n_var = n_col
cnLevels = ispan(7, 21, 1)
```

```
wks = gsn_open_wks("x11", "traj")
gsn_define_colormap(wks, "GMT_panoply")
cmap = gsn_retrieve_colormap(wks)
```

```
res = True ; mapping resources
res@mpLimitMode = "LatLon"
res@mpMaxLatF = 60
res@mpMinLatF = 0
res@mpMinLonF = -110
res@mpMaxLonF = 0
res@mpCenterLonF = -65
```

```
pres = True ; polyline resources
pres@gsLineThicknessF = 6.0 ; line thickness
```

```
mres = True ; marker resources
first = True
first@gsMarkerSizeF = 9.0
first@gsMarkerColor = "red"
```

```
19950804 12 31.2 265.6 1013.8 16.3 11.2 9.0 32.8 3.9 -4.2 4.6
19950804 18 31.7 264.9 1013.9 17.2 13.6 10.5 27.8 5.7 -2.6 5.5
19950805 00 32.1 264.4 1011.5 19.7 12.5 11.0 37.5 3.9 2.0 4.9
19950805 06 32.5 263.7 1012.7 16.3 18.5 8.9 36.5 4.9 -1.2 3.7
19950805 12 33.6 263.1 1013.7 13.7 7.7 7.0 27.9 5.3 -2.9 3.5
19950805 18 34.1 262.6 1013.3 14.2 18.0 9.1 28.5 5.6 -2.2 5.2
19950806 00 34.4 262.3 1011.6 17.8 18.2 8.8 32.8 4.4 2.6 4.1
19950806 06 35.2 262.5 1013.6 16.1 7.3 6.5 30.5 4.5 1.6 3.1
19950806 12 35.6 261.7 1015.3 11.8 6.6 5.9 21.4 4.9 -6.2 2.9
19950806 18 36.3 261.6 1015.5 11.7 8.4 7.9 31.1 4.9 -6.8 4.7
19950807 00 36.6 262.0 1013.9 13.2 10.3 7.5 34.2 4.7 -5.5 4.2
19950807 06 37.5 261.8 1016.8 13.2 5.4 3.6 23.7 3.3 -8.3 3.9
19950807 12 38.3 261.4 1016.6 10.3 4.4 3.5 28.0 3.9 -1.9 2.8
19950807 18 38.8 261.8 1016.1 18.0 7.8 7.5 24.5 3.4 -4.3 4.2
19950808 00 39.3 262.0 1014.1 11.8 9.4 7.6 21.2 3.4 -3.3 4.4
19950808 06 41.0 259.9 1014.9 21.1 8.0 8.0 1.9 3.0 5.6 2.8
19950808 12 47.2 259.0 1008.7 17.3 9.1 8.4 20.0 6.1 -11.7 -1.6
19950808 18 49.7 268.6 1007.7 19.7 11.5 10.9 4.8 7.3 -14.1 -1.7
19950809 00 58.3 262.9 1007.2 19.3 12.9 11.1 6.4 5.3 -14.4 -1.4
19950809 06 58.8 263.6 1006.9 18.9 10.7 9.8 16.7 5.6 -15.7 -0.8
19950809 12 53.1 266.8 1006.6 17.4 6.5 5.9 5.1 4.7 -17.8 -0.8
19950809 18 53.7 269.5 1003.1 17.9 8.3 8.3 9.5 5.2 -17.7 -0.6
19950810 00 54.9 272.7 999.4 18.3 12.0 9.5 13.3 4.9 -12.0 -0.8
19950810 06 56.4 275.6 997.2 17.8 14.6 13.0 12.4 3.9 -13.2 -1.9
19950810 12 57.8 282.4 997.3 19.0 21.9 11.1 18.7 1.8 -16.0 0.2
19950810 18 57.2 289.7 994.3 25.6 16.8 15.8 34.7 4.1 -28.6 1.7
19950811 00 56.8 296.9 995.1 38.9 14.6 12.1 41.5 3.9 -19.7 2.8
19950811 06 53.8 303.5 997.1 38.8 16.0 14.3 47.2 6.2 -17.0 1.2
```

47

Reading ASCII Data: Trajectory


```
mres = True ; marker resources
first = True
first@gsMarkerSizeF = 9.0
first@gsMarkerColor = "red"
```

```
map = gsn_csm_map_ce(wks,res)
```

```
n_pt = numAsciiRow(flnm)
data = asciiread(flnm, (/n_pt,n_var/), "float")
lat = data (:,2)
lon = data (:,3)
var = data (:,7)
```

```
do j = 0, n_pt - 2
  ; assign a color based upon an input scalar variable
  pres@gsLineColor = GetFillColor(cnLevels,cmap,avg((/var(j),var(j+1)/)))
  gsn_polyline(wks,map, (/lon(j),lon(j+1)/), (/lat(j),lat(j+1)/), pres)
end do
gsn_polymarker(wks,map,lon(0),lat(0),first) ; draw start of trajectory

draw(map)
end
```



48

Writing ASCII Data

```
t2_point = a->T2(:,locY,locX)
q2_point = a->Q2(:,locY,locX)

asciwrite ("t2.txt" , t2_point)
asciwrite ("q2.txt" , sprintf("%9.3f", q2_point))

npts = dimsizes(t2_point)
data = new( npts, "string")
do npt=0,npts-1
    data(npt) = sprintf("%7.1f ", t2_point(npt))
    data(npt) = data(npt) + sprintf("%7.1f ", q2_point(npt))
end do
asciwrite ("t2_q2.txt", data)

data2 = new((/npts,2/),"float")
data2(:,0) = t2_point
data2(:,1) = q2_point
write_matrix(data2,"2f7.3",True)
```

write_matrix

49

Shapefiles and WRF

- A geospatial vector data format for GIS systems software
- We can use it to mask data to specific regional or state borders, rather than drawing a box over an area
- Shapefiles can have three different types of data:
 - Point (locations of cities or places of interest, population data, election data)
 - Polyline (non-closed boundaries like rivers and roads)
 - Polygon (closed geographic boundaries like countries, states, provinces, territories, and lakes)
 - Only one data type per shapefile!

50

Shapefiles and WRF

```
shp_filename = "cb_2014_us_state_20m.shp"
f = addfile(shp_filename, "r")
print(f) ; print shapefile metadata

id = f->NAME ; we know we want the states,
; so read and print the metadata
```

```
print(id)

Variable: f
Type: file
Filename: cb_2014_us_state_20m
Path: /glade/scratch/robert/Ensembles/T2/Shapefiles/Shapefiles_US/cb_2014_us_state_20m.shp
File global attributes:
    layer_name : cb_2014_us_state_20m
    geometry_type : polygon
    geom_sindex : 0
    geom_numpts : 1
    segs_xyindex : 0
    segs_xumpts : 1
Dimensions:
    geometry : 2
    segments : 2
    num_features : 52 // unlimited
    num_segments : 132
    num_points : 13785
Variables:
    integer geometry ( num_features, geometry )
    integer segments ( num_segments, segments )
    double x ( num_points )
    double y ( num_points )
    double z ( num_points )
    string STATEFP ( num_features )
    string STATENS ( num_features )
    string APOGEOID ( num_features )
    string GEOID ( num_features )
    string STUOPS ( num_features )
    string NAME ( num_features )
    string LSAD ( num_features )
    double ALAND ( num_features )
    double AWATER ( num_features )
```

```
Variable: id
Type: string
Total Size: 416 bytes
52 values
Number of Dimensions: 1
Dimensions and Sizes: (num_features | 52)
Coordinates:
Number of Attributes: 0
(1) California
(2) District of Columbia
(3) Florida
(4) Idaho
(5) Illinois
(6) Iowa
(7) Kentucky
(8) Louisiana
(9) Maryland
(10) Michigan
(11) Minnesota
(12) Missouri
(13) New York
(14) Oregon
(15) Tennessee
(16) Texas
(17) Virginia
(18) Wisconsin
(19) Alaska
(20) Arizona
(21) Arkansas
(22) Colorado
(23) Indiana
(24) Connecticut
(25) Hawaii
(26) Nebraska
(27) New Mexico
(28) North Carolina
(29) Ohio
(30) Maine
(31) Massachusetts
(32) Mississippi
(33) Montana
(34) Oklahoma
(35) South Carolina
(36) South Dakota
(37) Utah
(38) Washington
(39) West Virginia
(40) Wyoming
(41) Delaware
(42) Rhode Island
(43) Alabama
(44) North Dakota
(45) Pennsylvania
(46) Vermont
(47) Puerto Rico
(48) Kansas
(49) Nevada
(50) New Hampshire
(51) New Jersey
```

51

Shapefiles and WRF

```
a = addfile("wrfout_d01_2000-07-17_00:00:00.nc","r")
wks = gsn_open_wks("X11","OK_TX")
var = a->T2(0,:,:)
var@lat2d = a->XLAT(0,:,:)
var@lon2d = a->XLONG(0,:,:)
shp_filename = "cb_2014_us_state_20m.shp" ; Shapefile from internet
opt = True
opt@shape_var = "NAME" ; We know the variable name
opt@shape_names = (/ "Oklahoma", "Texas" /) ; The states we want to mask
var_mask = shapefile_mask_data(var,shp_filename,opt) ; Mask the data
pltres = True
pltres@PanelPlot = True ; We need a panel plot to plot more than one state
mpres = True
mpres@Zoomin = True ; We want to zoom on our area of interest
mpres@Xstart = 150 ; Grid points of the zoomed in area
mpres@Ystart = 135
mpres@Xend = 200
mpres@Yend = 185
var_mask_zoom = var_mask(y_start:y_end,x_start:x_end) ; Zoomed in variable
; Make contours, draw them on a map, then draw the outline of the polygons
opts = True
opts@cnFillOn = True
contour_mask = wrf_contour(a,wks,var_mask,opts)
plot_mask = wrf_map_overlays(a,wks,contour_mask,pltres,mpres)
id_mask = gsn_add_shapefile_polygons(wks,plot_mask,shp_filename,True)
draw(plot_mask)
frame(wks)
```


52

Shapefiles and WRF

```

a = addfile("wrfout_d01_2000-07-17_00:00:00.nc","r")
wks = gsn_open_wks("X11","OK_TX")
var = a->T2(0,,:,)
var@lat2d = a->XLAT(0,,:,)
var@lon2d = a->XLONG(0,,:,)
shp_filename = "cb_2014_us_state_20m.s"
opt = True
opt@shape_var = "NAME" ; We know the v
opt@shape_names = ("/Oklahoma","Texas")
var_mask = shapefile_mask_data(var,shp)
pltres = True
pltres@PanelPlot = True ; We need a pa
mpres = True
mpres@Zoomin = True ; We want to zoom
mpres@Xstart = 150 ; Grid points of th
mpres@Ystart = 135
mpres@Xend = 200
mpres@Yend = 185
var_mask_zoom = var_mask(y_start:y_end
; Make contours, draw them on a map, t
opts = True
opts@cnFillOn = True
contour_mask = wrf_contour(a,wks,var_m
plot_mask = wrf_map_overlays(a,wks,contour_mask,pltres,mpres)
id_mask = gsn_add_shapefile_polylines(wks,plot_mask,shp_filename,True)
draw(plot_mask)
frame(wks)

```



53

Geo Referenced Graphics

54

```

load "$NCARG_ROOT/lib/ncarg/nclscripts/csm/gsn_code.ncl"
load "$NCARG_ROOT/lib/ncarg/nclscripts/wrf/WRFUserARW.ncl"

begin
a = addfile("./wrfout_d01_2012-09-28_00:00:00.nc","r")
wks = gsn_open_wks("X11","plt_Surface")

T2 = wrf_user_getvar(a,"T2",-1)
times = wrf_user_getvar(a,"times",-1)
ntimes = dimsizes(times)

mpres = True
pltres = True

do it=0,ntimes-1
  opts = True
  opts@cnFillOn = True
  contour_t2 = wrf_contour(a,wks,T2(it,,:,),opts)
  plot = wrf_map_overlays(a,wks,(/contour_t2/),pltres,mpres)

end do

end

```

55

```

load "$NCARG_ROOT/lib/ncarg/nclscripts/csm/gsn_code.ncl"
load "$NCARG_ROOT/lib/ncarg/nclscripts/wrf/WRFUserARW.ncl"
load "$VAPOR_HOME/share/examples/NCL/wrf2geotiff.ncl"

begin
a = addfile("./wrfout_d01_2012-09-28_00:00:00.nc","r")
wks = gsn_open_wks("ps","plt_Surface")
wrf2geotiff = wrf2geotiff_open(wks)

T2 = wrf_user_getvar(a,"T2",-1)
times = wrf_user_getvar(a,"times",-1)
ntimes = dimsizes(times)

mpres = True
pltres = True
pltres@gsnFrame = False

do it=0,ntimes-1
  opts = True
  opts@cnFillOn = True
  contour_t2 = wrf_contour(a,wks,T2(it,,:,),opts)
  plot = wrf_map_overlays(a,wks,(/contour_t2/),pltres,mpres)
  wrf2geotiff_write(wrf2geotiff,a,times(it), wks, plot, False)
  frame(wks)
end do

wrf2geotiff_close(wrf2geotiff, wks)
end

```

56

Linking NCL to Fortran/C Code

- Link Fortran/C code to NCL scripts
 - Create a library from your Fortran/C code
 - Link to NCL script
- Link low-level NCL (NCAR Graphics) to Fortran code
 - Add calls to code inside Fortran code
 - Compile Fortran code with NCL libraries
 - Example: WPS/utls/plotfmt.exe
 - *Older way of creating plots – not recommended*

57

Linking NCL to Fortran/C Code

- Easier to use F77 code, but works with F90 code
- Need to isolate definition of input variables and wrap them with special comment statements:

```
C  NCLFORTSTART
C  NCLEND
```

- Use a tool called **WRAPIT** to create a ***.so** file
 - > WRAPIT myTK.f
- Load the ***.so** file into the NCL script with “**external**” statement
- Call Fortran function with special “**::**” syntax
- You must pre-allocate for arrays!

58

Linking NCL to Fortran/C Code: myTK.f

```
C  NCLFORTSTART
  subroutine compute_tk (tk,pressure,theta, nx, ny, nz)
    implicit none
    integer nx,ny,nz
    real pi, tk(nx,ny,nz)
    real pressure(nx,ny,nz), theta(nx,ny,nz)
C  NCLEND
    integer i,j,k

    do k=1,nz
      do j=1,ny
        do i=1,nx
          pi=(pressure(i,j,k) / 1000.)*(287./1004.)
          tk(i,j,k) = pi*theta(i,j,k)
        enddo
      enddo
    enddo

  end
```

59

myTK.so – Create & use in NCL Script

```
% WRAPIT myTK.f
```

This will create a “**myTK.so**” file

```
load "$NCARG_ROOT/lib/ncarg/nclscripts/csm/gsn_code.ncl"
load "$NCARG_ROOT/lib/ncarg/nclscripts/wrf/WRFUserARW.ncl"
external myTK "./myTK.so"

begin
  t = wrf_user_getvar(a,"T",5)

  t = t + 300
  p = wrf_user_getvar(a,"pressure",5)

  ; Must preallocate space for output arrays
  dim = dimsizes(t)
  tk = new( dimsizes(t), typeof(t) )

  ; Remember, Fortran/NCL arrays are ordered differently
  myTK :: compute_tk (tk,p,t,dim(2),dim(1),dim(0))
end
```

60

FORTRAN 90 Code

- Can use simple FORTRAN 90 code
- Your FORTRAN 90 program may not contain any of the following features:
 - pointers or structures as arguments,
 - missing/optional arguments,
 - keyword arguments, or
 - recursive procedure.

61

Compiling with NCL

```
In function `write_png':  
  undefined reference to `png_create_write_struct'  
  undefined reference to `png_create_info_struct'  
  undefined reference to `png_destroy_write_struct'  
  undefined reference to `png_destroy_write_struct'
```

```
-L<path_to_png_lib> -lpng -L<path_to_z_lib> -lz
```

```
/usr/local/ncl/lib/libncarg.a(agcurv.o): In function `agcurv':  
agcurv.f:(.text+0x69): undefined reference to `_gfortran_copy_string'  
/usr/local/ncl/lib/libncarg.a(aggctch.o): In function `aggctch':  
aggctch.f:(.text+0x3e): undefined reference to `_gfortran_copy_string'  
aggctch.f:(.text+0x7b): undefined reference to `_gfortran_copy_string'
```

```
-L<path_to_gfortran_lib> -lgfortran
```

62

NCL Support

- wrfhelp@ucar.edu
all questions about WRF and NCL

- ncl-talk@ucar.edu
generic NCL questions

63