WRF Software: Code and Parallel Computing	Outline WRF architecture – driver, mediation, model Need and design for parallelism Communication patterns to support parallelism
John Michalakes, WRF Software Architect Dave Gill	 Directory structure and file location overview Model layer interface The "grid" struct Indices Dereferencing I/O
 Introduction – WRF Software Characteristics Developed from scratch beginning around 1998, primarily Fortran 	Introduction - WRF Software Framework Overview Implementation of WRF Architecture
 and C Requirements emphasize flexibility over a range of platforms, applications, users, performance WRF develops rapidly. First released Dec 2000 Supported by flexible efficient architecture and implementation called the WRF Software Framework 	 Hierarchical organization Multiple dynamical cores Plug compatible physics Abstract interfaces (APIs) to external packages Performance-portable Designed from beginning to be adaptable to today' s computing environment for NWP http://mmm.ucar.edu/wrf/WG2/bench/

WRF Software Architecture



- Hierarchical software architecture
 - Insulate scientists' code from parallelism and other architecture/ implementation-specific details
 - Well-defined interfaces between layers, and external packages for communications, I/O, and model coupling facilitates code reuse and exploiting of community infrastructure, e.g. ESMF.

WRF Software Architecture



- Driver Layer
 - Domains: Allocates, stores, decomposes, represents abstractly as single data objects
 - Time loop: top level, algorithms for integration over nest hierarchy

WRF Software Architecture



Mediation Layer

- Solve routine, takes a domain object and advances it one time step
- Nest forcing, interpolation, and feedback routines

WRF Software Architecture



- Mediation Layer
 - The sequence of calls for doing a time-step for one domain is known in Solve routine
 - Dereferences fields in calls to physics drivers and dynamics code
 - Calls to message-passing are contained here as part of Solve routine

WRF Software Architecture



- Model Layer
 - Physics and Dynamics: contains the actual WRF model routines are written to perform some computation over an arbitrarily sized/ shaped, 3d, rectangular subdomain

Call Structure Superimposed on Architecture





APPLICATION SYSTEM HARDWARE

- Fundamentally, processors haven't changed much since 1960
- Quantitatively, they haven't improved nearly enough
 - 100,000x increase in peak speed
 - 100,000x increase in memory size
- We make up the difference with parallelism
 - Ganging multiple processors together to achieve 10¹¹⁻¹² flop/second
 - Aggregate available memories of 10¹¹⁻¹² bytes

~1,000,000,000,000 flop/s ~2500 procs 48-h,12-km WRF CONUS in under 15 minutes

WRF Domain Decomposition

- The WRF model decomposes domains horizontally
- For *n* MPI tasks, the two nearest factors (*n*= *k* * *m*)are selected; the larger is used to decompose the y-direction, the smaller is used to decomposed the x-direction
- Users may choose a preferred decomposition (nproc_x, nproc_y)
- Prime numbers and composites with large prime factors are usually to be avoided
- The behavior of 132 vs 131, and 200 vs 202 are quite different

5,140 120 5000 4,321 100 4000 Simulation Speec Gflop/second 80 3000 60 Intel Xeon 5670 (6 core) 2000 -Intel Xeon 5560 (4 core) 40 Cray XT5 1000 -Sun/AMD (Ranger) 20 0 1024 2048 3072 4096 5120 6144 7168 8192 9216 0 Number of cores

140

6000

January 2000 Benchmark - 1 task: 74x61



January 2000 Benchmark - 64 tasks: 10x8

January 2000 Benchmark

- 74x61 grid cells
- 1 hour forecast, 3 minute time step, 20 time step average
- IO excluded

Decomposed domain sizes proc count: I-dim x J-dim

1: 74x61	2: 74x31	4: 37x31	8: 37x16
16: 19x16	32: 19x8	64: 10x8	

WRF Domain Decomposition

- As you increase the number of total MPI tasks, you reduce the amount of work inside of each MPI task
- The amount of time to process communication between MPI tasks tends to be *at best* constant
- As more MPI tasks are involved, more contention for hardware resources due to communication is likely
- As the computation time gets smaller compared to the communications time, parallel efficiency suffers

January 2000 Benchmark

Pro	cessor Count	SM — OpenMP % Efficiency	DM — MPI % Efficiency
1	74x61	100	100
2	74x31	72	98
4	37x31	65	91
8	37x16	31	83
16	19x16	16	70
32	19x8	8	56
64	10x8	3	40









Where are WRF source code files located?	Where are WRF source code files located?
All of the differences between the .F and .f90 files are due to the included pieces that are manufactured by the Registry. These additional pieces are all located in the WRFV3/inc directory. For a serial build, almost 450 files are manufactured. Usually, most developers spend their time working with physics schemes.	 The "main" routine that handles the calls to all of the physics and dynamics: WRFV3/dyn_em/solve_em.F This "solver" is where the tendencies are initialized to zero, some pre-physics terms are computed, and the time stepping occurs The calls to most of the physics schemes are made from a further call down the call tree dyn_em/module_first_rk_step_part1.F
Where are WRF source code files located?	Where are WRF source code files located?
Where are WRIP source code mes located?	
 Inside of solve_em and first_rk_step_part1, all of the data is located in the "grid" structure: grid%ht. The dimensions in solve_em and first_rk_step_part1 are "d" (domain), and "m" (memory): 	 If you are interested in looking at physics, the WRF system has organized the files in the WRFV3/phys directory. In WRFV3/phys, each type of physics has a driver: module_cumulus_driver.F cu

Where are WRF source code files located?	Where are WRF source code files located?
 The subgrid-scale precipitation (*_cu_*.F) module_cu_bmj.F module_cu_camzm.F module_cu_g3.F module_cu_gd.F module_cu_kf.F module_cu_kfeta.F module_cu_nsas.F module_cu_osas.F module_cu_sas.F module_cu_tiedtke.F 	 Advection WRFV3/dyn_em/module_advect_em.F Lateral boundary conditions WRFV3/dyn_em/module_bc_em.F
 Where are WRF source code files located? Compute various RHS terms, pressure gradient, buoyancy, w damping, horizontal and vertical diffusion, Coriolis, curvature, Rayleigh damping WRFV3/dyn_em/module_big_step_utilities_em.F All of the sound step utilities to advance u, v, mu, t, w within the small time-step loop WRFV3/dyn_em/module_small_step_em.F 	WRF Model Layer Interface – The Contract with Users All state arrays passed through argument list as simple (not derived) data types Domain, memory, and run dimensions passed unambiguously in three dimensions Model layer routines are called from mediation layer (physics drivers) in loops over tiles, which are multi-threaded





WRF I/O

- Streams (similar to Fortran units): pathways into and out of model
- Can be thought of as files, though that is a restriction
 - History + auxiliary output streams (10 and 11 are reserved for nudging)
 - Input + auxiliary input streams (10 and 11 are reserved for nudging)
 - Restart, boundary, and a special DA in-out stream
 - Currently, 24 total streams
 - Use the large values and work down to stay away from "used"
 - Non-chemistry: use history streams 13-22, 24
 - $-\,$ Chemistry: use history streams 20, 21, 22, 24 $\,$

WRF I/O

- Attributes of streams
 - Variable set
 - The set of WRF state variables that comprise one read or write on a stream
 - Defined for a stream at compile time in Registry
 - Format
 - The format of the data outside the program (e.g. NetCDF), split
 - Specified for a stream at run time in the namelist

WRF I/O

- Attributes of streams
 - Additional namelist-controlled attributes of streams
 - Dataset name
 - Time interval between I/O operations on stream
 - Starting, ending times for I/O (specified as intervals from start of run)

WRF I/O

- Attributes of streams
 - Mandatory for stream to be used:
 - Time interval between I/O operations on stream
 - Format: io_form

Example 1: Add output without recompiling

Edit the namelistinput file, the time_control namelist record
 iofields_filename = "myoutfields.txt" (MAXDOM)
 io_form_auxhist24 = 2 (choose an available stream)
 auxhist24_interval = 10 (MAXDOM, every 10 minutes)

Place the fields that you want in the named text file myoutfields.txt
 +: h: 24: RAINC, RAINNC

• Where "+" means ADD this variable to the output stream, "h" is the history stream, and "24" is the stream number

Outline

- WRF architecture driver, mediation, model
- Need and design for parallelism
- Communication patterns to support
 parallelism
- Directory structure and file location overview
- Model layer interface
 - The "grid" struct
 - Indices
 - Dereferencing
- I/O