



# Advanced Usage of the WRF Preprocessing System

Michael Duda



The WRF Users' Basic Tutorial  
28 January - 1 February 2019, Boulder

\*NCAR is sponsored by the  
National Science Foundation

## Outline

- The GEOGRID.TBL file
  - What is the GEOGRID.TBL file?
  - Ingesting new static fields
  - Examples: Using high-resolution land use and topography data
- The METGRID.TBL file
  - What is the METGRID.TBL file?
  - Example: Defining interpolation options for a new field
  - Example: Using the METGRID.TBL file for a real-time system
- Utility programs example: fixing "hot lakes"



The WRF Users' Basic Tutorial  
28 January - 1 February 2019, Boulder

2

## The GEOGRID.TBL File

- GEOGRID.TBL is the file that determines which fields are interpolated by geogrid *at runtime*
  - Each entry in GEOGRID.TBL corresponds to one field to be produced by geogrid
  - When new data sources are involved, or when the default treatment of fields is inadequate, user may want/need to edit GEOGRID.TBL
  - However, default GEOGRID.TBL is sufficient to initialize a WRF simulation



The WRF Users' Basic Tutorial  
28 January - 1 February 2019, Boulder

3

## The GEOGRID.TBL File

- Format of GEOGRID.TBL file is simple text, with specifications of the form *keyword=value*
- Example entry for a 30" landuse data set:

```
=====
name=LANDUSEF    # Houston, TX urban data
priority         = 2
dest_type        = categorical
z_dim_name       = land_cat
interp_option    = 30s:nearest_neighbor
abs_path         = 30s:/users/duda/Houston/
=====
```

For a complete list of possible keywords [See p. 3-46](#)



The WRF Users' Basic Tutorial  
28 January - 1 February 2019, Boulder

4

## The GEOGRID.TBL File

- Using the GEOGRID.TBL, we can
  - Change the method(s) used to interpolate a field
  - Apply smoothing filters to continuous fields
  - Derive fields from others
    - E.g., dominant category or slope fields
  - *Add new data for geogrid to interpolate*



## New Fields in GEOGRID.TBL

There are three basic types of new data to be added through the GEOGRID.TBL file:

- 1) Completely new fields
  - fields that were previously not processed by geogrid
- 2) Different resolution data sets for an existing field
  - Such sources *do not need to be supplemented* by existing data
  - E.g., Adding a 90-meter resolution topography data set
- 3) Alternative sources for a field that *must be used in addition to an existing source*
  - E.g., A new soil category data set exists, but covers only South Korea



## 1) Completely new fields

Completely new fields:

*For a new field, simply add an entry in GEOGRID.TBL for that field.*

```
=====
name = MY_NEW_FIELD_NAME
priority = 1
dest_type = continuous
interp_option = four_pt
abs_path = /data/duda/mydata/
=====
```

Annotations:

- Name of field that this entry is for (points to `name`)
- Priority of this data source compared with other sources for same field (points to `priority`)
- How to interpolate this field (points to `interp_option`)
- Where on disk to find the data for this field (points to `abs_path`)

See p. 3-46



## 2) Different resolution data set

Different resolution data sets for an existing field:

*Specify the path to the new data set and which interpolation methods should be used for the new resolution in the existing entry for that field.*

```
=====
name = HGT_M
priority = 1
dest_type = continuous
smooth_option = smth-desmth
interp_option = 30s:special(4.0)+four_pt
interp_option = my_res:four_pt
interp_option = default:four_pt
rel_path= 30s:topo_30s/
rel_path= my_res:new_topo_directory/
rel_path= default:topo_2m/
=====
```



### 3) Alternative data sources

Alternative sources for a field that must be used in addition to an existing source :

*Add a new entry for the field that has the same name as the field's existing entry, but make priority of new entry higher.*

```
=====
name = HGT_M
  priority = 2
  dest_type = continuous
  interp_option = default:four_pt
  rel_path      = default:some_path/
=====
name = HGT_M
  priority = 1
  dest_type = continuous
  interp_option = default:four_pt
  rel_path      = default:topo_2m/
=====
```



9

### Preparing new geogrid data sets

To add a new data source, we need to

- 1) Write the data in the proper binary format
  - See Chapter 3: "Writing Static Data to the Geogrid Binary Format"
  - Can make use of [read\\_geogrid.c](#) and [write\\_geogrid.c](#)
- 2) Create an "index" metadata file for the data set
  - This tells geogrid about the projection, coverage, resolution, type, and storage representation of the data set
- 3) Add/edit entry for the data in the GEOGRID.TBL file
  - The change to GEOGRID.TBL will follow one of the three cases mentioned before



The WRF Users' Basic Tutorial  
28 January - 1 February 2019, Boulder

10

### The Geogrid Data Format


The geogrid format is a simple binary raster

- Elements of a rectangular array of data are written, row by row, to a file
- No record markers or any type of metadata are written to this file

a <sub>43</sub>	a <sub>44</sub>	a <sub>45</sub>	a <sub>46</sub>	a <sub>47</sub>	a <sub>48</sub>
a <sub>37</sub>	a <sub>38</sub>	a <sub>39</sub>	a <sub>40</sub>	a <sub>41</sub>	a <sub>42</sub>
a <sub>31</sub>	a <sub>32</sub>	a <sub>33</sub>	a <sub>34</sub>	a <sub>35</sub>	a <sub>36</sub>
a <sub>25</sub>	a <sub>26</sub>	a <sub>27</sub>	a <sub>28</sub>	a <sub>29</sub>	a <sub>30</sub>
a <sub>19</sub>	a <sub>20</sub>	a <sub>21</sub>	a <sub>22</sub>	a <sub>23</sub>	a <sub>24</sub>
a <sub>13</sub>	a <sub>14</sub>	a <sub>15</sub>	a <sub>16</sub>	a <sub>17</sub>	a <sub>18</sub>
a <sub>7</sub>	a <sub>8</sub>	a <sub>9</sub>	a <sub>10</sub>	a <sub>11</sub>	a <sub>12</sub>
a <sub>1</sub>	a <sub>2</sub>	a <sub>3</sub>	a <sub>4</sub>	a <sub>5</sub>	a <sub>6</sub>

8 rows

6 columns



See p. 3-37

*A file containing a  $N \times M$  array, with each element represented using  $K$  bytes, should have size exactly  $N * M * K$  bytes!*



The WRF Users' Basic Tutorial  
28 January - 1 February 2019, Boulder

11

### The Geogrid Data Format

Since the contents of the file contain only the values from the array, *care must be taken if using Fortran to write the array*

- Fortran unformatted writes add *record markers* to the beginning and end of each record
- So, rather than  $X_1 X_2 X_3 \dots X_{n-1} X_n$  we get  $R X_1 X_2 X_3 \dots X_{n-1} X_n R$ , where  $R$  is a record marker

Instead of Fortran, the C routines [read\\_geogrid.c](#) and [write\\_geogrid.c](#) may be used to read and write binary files

- these may be called from either Fortran or C



The WRF Users' Basic Tutorial  
28 January - 1 February 2019, Boulder

12

## The Geogrid Data Format

From python, one can use

```
numpy.fromfile(file, dtype=dt)
```

to read the geogrid binary files, and

```
numpy.ndarray.tofile(file)
```

to write the geogrid binary files.

The `dtype` argument and `numpy.ndarray.astype` may be used to match the *wordsize* and *endianness* used in the binary file!

- Values are always represented as integers



## The Geogrid Data Format

The filenames of geogrid binary files should have the form:

xxxxx-XXXXX.yyyyy-YYYYY

where

xxxxx	is the starting x-index
XXXXX	is the ending x-index
yyyyy	is the starting y-index
YYYYY	is the ending y-index

E.g., For a binary file containing an array with 500 columns and 750 rows, the file name would be


00001-00500.00001-00750



## The Geogrid Data Format

If the data are not available in a single tile (array), multiple files may be used to store the data

- All tiles must have the same x-dimension
- All tiles must have the same y-dimension
- If necessary, a tile can be "padded" with missing values to expand it to the same size as other tiles in the data set



Tile A named 00001-01480.00001-01600

Tile B named 01481-02960.00001-01600

Tile C named 00001-01480.01601-03200



Tile D named 01481-02960.01601-03200



## The Geogrid Data Format


If the data do not cover a rectangular region, areas with no data are simply filled with a missing value so that the overall data set is rectangular

- The particular missing value used in the data set is specified in the `index` metadata file for the data set




## Example: Houston LU Data Set

- Given dataset for new Houston urban land use categories
  - Regular lat/lon projection, 30" resolution; categories 31, 32 & 33



Urban areas (black) using USGS 24-category data set



Area of Houston data tile in relation to model domain – white=missing data and blue=valid data



## Example: Houston LU Data Set

To make use of the new data, we do the following:

- 1) Write the data to the binary format used by geogrid
- 2) Create an index file for the data

```
type=categorical
category_min=31; category_max=33
projection=regular_ll
dx=0.00833333; dy=0.00833333
known_x=1.0; known_y=1.0
known_lat=29.3375
known_lon=-95.9958333
wordsize=1
tile_x=157; tile_y=143; tile_z=1
missing_value = 0.
units="category"
description="3-category urban LU"
```

Data set has categories 31 through 33

30 arc second resolution

Geographic location of data set

Treat 0 as "no data"

See p. 3-49



## Example: Houston LU Data Set

- 3) Define an entry for the data in GEOGRID.TBL

```
=====
name=LANDUSEF
priority    = 2
dest_type  = categorical
z_dim_name = land_cat
interp_option = default:nearest_neighbor
abs_path   = default:/users/duda/Houston/
=====
```

Give this data source priority over default data sources


How to interpolate this data source, and where to find it on disk




## Example: Houston LU Data Set

- 4) Run geogrid.exe

Any gridpoints covered by Houston data will use it; otherwise default USGS data will be used



Urban areas (black) using USGS 24-category data set



Augmented urban areas (red shades) using new LU data set




## Example: South Korea

Shuttle Radar Topography Mission (SRTM) 3 arc second topography data

We would like to use the SRTM data, especially for domains 2 and 3.

Follow steps for adding a new resolution for an existing data set (case 2)



## Example: Seoul

To use the SRTM topography data, we


- 1) Write data to geogrid binary format
- 2) Create an index file for the data set
- 3) Modify the GEOGRID.TBL entries for HGT\_M, HGT\_U, and HGT\_V

```
=====
name = HGT_M
priority = 1
dest_type = continuous
interp_option = default:average_gcell(4.0)+four_pt
interp_option = SRTM:four_pt
rel_path = default:gmted2010_30s/
rel_path = SRTM:SRTM/
=====
```


- 4) Specify that we should interpolate from SRTM in namelist by setting  
`geog_data_res = 'default', 'SRTM+default', 'SRTM+default'`



## Example: Seoul



Domain 3 (DX=111m) using default 30" GMTED2010 topography




Domain 3 (DX=111m) using 3" SRTM topography



## Another Example: Los Angeles

For Los Angeles, we have a 30-meter resolution, 3 urban land use category data set



## Outline

- The GEOGRID.TBL file
  - What is the GEOGRID.TBL file?
  - Ingesting new static fields
  - Examples: Using high-resolution land use and topography data
- The METGRID.TBL file
  - What is the METGRID.TBL file?
  - Example: Defining interpolation options for a new field
  - Example: Using the METGRID.TBL file for a real-time system
- Utility programs example: fixing “hot lakes”



## The METGRID.TBL File

The METGRID.TBL file controls how meteorological fields are interpolated

- Unlike GEOGRID.TBL, METGRID.TBL *does not determine which fields will be processed, only how to process them* if they are encountered
- Every field in intermediate files will be interpolated
  - If no entry in METGRID.TBL for a field, a default interpolation scheme (nearest neighbor) will be used
  - It is possible to specify in METGRID.TBL that a field should be discarded



## The METGRID.TBL File

- Suitable entries in METGRID.TBL are provided for common fields
  - *Thus, many users will rarely need to edit METGRID.TBL*
- When necessary, different interpolation methods (and other options) can be set in METGRID.TBL
  - Interpolation options can depend on the source of a field



## The METGRID.TBL File

- Example METGRID.TBL entry (for “soil moisture 0–10 cm”)

```
=====
name=SM000010
interp_option=sixteen_pt+four_pt+average_4pt
masked=water
interp_mask=LANDSEA(0)
fill_missing=1.
flag_in_output=FLAG_SM000010
=====
```





## Example: A new METGRID.TBL entry

- Suppose we have a 1000x1000 domain over Houston (dx=500 m)
  - This is the same domain as in the urban land use example
- Meteorological data come from 1-degree GFS
  - *Note that we will be interpolating 1-degree data onto a 500-m grid!*
- We want to create an entry for a new soil moisture field, SM000010




## Example: A new METGRID.TBL entry

- Initially, we run metgrid.exe and get the message:

```
INFORM: Entry in METGRID.TBL not found for field SM000010.  
Default options will be used for this field!
```

- The resulting SM000010 field looks very coarse
- We need to create a METGRID.TBL entry so metgrid will know how to interpolate this field!



## Example: A new METGRID.TBL entry

- We add an initial entry in METGRID.TBL for SM000010:

```
=====
name = SM000010
masked = water
interp_mask = LANDSEA(0)
interp_option = sixteen_pt + nearest_neighbor
fill_missing = 0.
=====
```

Specify that the field should *not* be interpolated to model water points

Specify that metgrid should not use points in source where LANDSEA field equals 0



Fill model points that don't receive an interpolated value (like water) to 0

For a complete list of possible keywords [See p. 3-52](#)



## Example: A new METGRID.TBL entry


- Now, after running metgrid.exe again, the SM000010 field looks like





## Example: A new METGRID.TBL entry

- But, the interpolated field still looks bad near the coastline



Should be sufficient data to use 4-point interpolation in these areas

Model grid points here should be adjacent to at least one valid GFS point (though not nearest)

Interpolated SM000010 field  
(*sixteen\_pt + nearest\_neighbor*)



## Example: A new METGRID.TBL entry

- Update the METGRID.TBL entry for SM000010


```
=====
name = SM000010
masked = water
interp_mask = LANDSEA(0)
interp_option = sixteen_pt + four_pt + average_4pt
fill_missing = 0.
=====
```

- If 16-pt doesn't work, then try 4-pt before reverting to a 4-point average
  - Note that 4-point average will work anywhere nearest\_neighbor would (missing/masked values not counted in the average)




## Example: A new METGRID.TBL entry

- The resulting field, below-left:



Interpolated SM000010 field  
(*sixteen\_pt + four\_pt + average\_4pt*)




Which interpolator was used at each  
model grid point




## Example: A new METGRID.TBL entry

- By using **wt\_average\_4pt** instead of **average\_4pt**:



*sixteen\_pt + four\_pt + average\_4pt*



*sixteen\_pt + four\_pt + wt\_average\_4pt*




## Outline

- The GEOGRID.TBL file
  - What is the GEOGRID.TBL file?
  - Ingesting new static fields
  - Examples: Using high-resolution land use and topography data
- The METGRID.TBL file
  - What is the METGRID.TBL file?
  - Example: Defining interpolation options for a new field
  - Example: Using the METGRID.TBL file for a real-time system
- Utility programs example: fixing “hot lakes”



## Motivating Problem

The “Hot Lake” problem: Inland water bodies that are not resolved by SST data sets often receive extrapolated values from nearby oceans or other resolved water bodies.



Above left: Skin temperature field (TSK) for Iceland and surrounding ocean on 26 January 2011 1200 UTC from NCEP GFS and RTG SST data.


Above right: TSK in the Mývatn region. SST for Mývatn Lake is ~277 K!



## Approach

In WRF v3.3 and later, let the *real* preprocessor know which water points are inland water bodies, and provide it a more accurate estimate of SST to be used only over these water bodies.

- 1) Identify inland water bodies in the land cover data set



- 1) Provide a suitable proxy for SST field over inland water bodies
  - E.g., Average surface air temperature for X days prior, 273 K for frozen lakes, etc.
- 2) Modify the SST field in the WRF input file
  - Use new capability in v3.3 real.exe program



## Identifying Lakes

Some data sets already identify lakes with separate categories

- MODIS, CORINE

For others, we need a way to do this

- Should be automated
  - don't want to spend long hours clicking on pixels for each data set
- Should be tunable
  - what constitutes a lake will naturally depend on what our SST data set is able to resolve
- Ideally, would not require auxiliary data

This is the default  
as of WPS v3.9

In *namelist.wps*, set:


- `geog_data_res = "usgs_lakes+default"` for USGS land use (16=ocean, 28=lake)
- `geog_data_res = "modis_30s_lake+default"` for MODIS land use (17=ocean, 21=lake)



## Creating a Proxy SST Field


The *avg\_tsfc.exe* utility program may be used to compute the average 2-m air temperature field for any number of full diurnal cycles

- Number of cycles determined by available intermediate files and date range in namelist
- The resulting TAVGSFC intermediate file may be provided to the metgrid program



## Test case: Lake Mývatn

To confirm that everything is working as expected, try correcting the temperature for Lake Mývatn in the winter



Grid ID	Resolution	Size
1	16 km	99x99
2	4 km	208x172
3	1 km	136x128
4	250 m	160x160

ICs + BCs from NCEP GFS


Sea surface temperatures from RTG SST

Initial time: 26 January 2011, 1200 UTC



## Test case: Lake Mývatn

26 January 2011, 12 UTC




Initial skin temperature field using extrapolated SST values

Initial skin temperature field using previous 5-day average of 2-m air temperature for lake SST



## Test case: Lake Mývatn

Time series of sensible heat flux in the center of the lake show a significant decrease when using a more realistic SST (TAVGSFC)



Latent heat flux time series from simulation using TAVGSFC for SST also shows a decrease from RTG SST time series as well



## Summary

- In this lecture, we've seen
  - What the GEOGRID.TBL and METGRID.TBL files do
  - How to use new geographical data sources in the WPS
    - High-resolution land use and topography data
  - How to use the METGRID.TBL file to correct interpolation-related problems
  - How utility programs can be used to improve simulations
- For other features of the WPS, see Chapter 3 of the User's Guide
- For more information about using high-resolution topography data or urban land use data (over the U.S.), see  
[http://www2.mmm.ucar.edu/people/duda/files/how\\_to\\_hires.html](http://www2.mmm.ucar.edu/people/duda/files/how_to_hires.html)



## Questions?



## Bonus slides: A second METGRID.TBL example



## METGRID.TBL: Real-time System Example

- Suppose we have a real-time system that:
  - Uses GFS for initial and boundary conditions
  - When possible (i.e., if the files are available soon enough) uses *soil moisture* and *soil temperature* fields from AGRMET
- In our system, it may occasionally happen that the AGRMET files are not ready when we want to start our WRF run
  - Because system is real-time, we want to proceed using just the GFS land surface fields!



## METGRID.TBL: Real-time System Example

- We already know how to run ungrib on multiple sources of data to get

*GFS:YYYY-MM-DD\_HH*

and

*AGRMET:YYYY-MM-DD\_HH*

intermediate files, and specify

`fg_name = 'GFS', 'AGRMET',`

in the `&metgrid` namelist record to use both sources

See p. 3-24



## METGRID.TBL: Real-time System Example

Without further changes, what happens if:

*Only GFS data are available when we run metgrid*

Metgrid runs and warns that no AGRMET data files were found:


```
Processing 2012-04-01_00
  GFS
  AGRMET
WARNING: Couldn't open file AGRMET:2012-04-01_00 for
input.
```

Metgrid will finish, but will only use GFS data!



## METGRID.TBL: Real-time System Example

And the 0-10 cm soil moisture field (SM000010) looks like:




## METGRID.TBL: Real-time System Example

However, what happens if:

*Both GFS and AGRMET files are available when we run metgrid?*

Our SM000010 field looks like:



We get unreasonable values with magnitude  $\sim 1E30$  near land-water boundaries!



## METGRID.TBL: Real-time System Example

*Why are there bad values near coastlines? What went wrong?*

In both Vtable.GFS and Vtable.AGRMET, the land-sea mask field is named LANDSEA

- In METGRID.TBL, our entry for SM000010 says:

```
=====
name=SM000010
interp_option=sixteen_pt+four_pt+wt_average_4pt+search
masked=water
interp_mask=LANDSEA(0)
fill_missing=1.
flag_in_output=FLAG_SM000010
=====
```



## METGRID.TBL: Real-time System Example

```
=====
name=SM000010
interp_option=sixteen_pt+four_pt+wt_average_4pt+search
masked=water
interp_mask=LANDSEA(0)
fill_missing=1.
flag_in_output=FLAG_SM000010
=====
```


After metgrid reads in LANDSEA from GFS file *to use as an interpolation mask*, it ignored the LANDSEA field from AGRMET *for use as a mask*.

- So, metgrid used the GFS LANDSEA mask even when interpolating AGRMET data!



## METGRID.TBL: Real-time System Example

When metgrid interpolated SM000010, it used the GFS landmask for a field masked by the AGRMET landmask!



*GFS LANDSEA field*



*AGRMET LANDSEA field*

*Note the disagreement between the two data sources near coastlines.*



## METGRID.TBL: Real-time System Example

**Solution:**

- Rename LANDSEA to *AGR LAND* in Vtable.AGRMET
- Rename LANDSEA to *GFS LAND* in Vtable.GFS
- Create separate entries in METGRID.TBL
  - one for GFS SM000010 field
  - another for AGRMET SM000010 field



## METGRID.TBL: Real-time System Example


```
=====
name=SM000010; from_input=GFS
interp_option=sixteen_pt+four_pt+wt_average_4pt+search
masked=water
interp_mask=GFS_LAND(0)
fill_missing=1.
flag_in_output=FLAG_SM000010
=====
```

```
=====
name=SM000010; from_input=AGRMET
interp_option=sixteen_pt+four_pt+wt_average_4pt+search
masked=water
interp_mask=AGR_LAND(-1.E30)
fill_missing=1.
flag_in_output=FLAG_SM000010
=====
```




## METGRID.TBL: Real-time System Example

With modified Vtables and METGRID.TBL:



*The SM000010 field when only  
GFS files are available*



*The SM000010 field when both GFS  
and AGRMET files are available*

