

# WRFDA Background Error Estimation

Syed RH Rizvi

*National Center For Atmospheric Research*  
**NCAR/ESSL/MMM, Boulder, CO-80307, USA**

*rizvi@ucar.edu*



# Talk overview

- What is Background Error (BE) ?
- Properties of BE
- Role of BE in WRFDA
- Various components of BE
- Impact of BE on minimization and forecasts
- How to compute (“gen\_be” utility)?
- Single Observation Test
- Upcoming new features
- Introduction to Practice Session

# What is BE?

- The BE covariance matrix describes the PDF of forecasts errors
- In practice it is simply taken as Gaussian-shaped distribution
- It is the covariance of (forecast - truth) in analysis control variable space

$$BE = \langle (x - x^t), (x - x^t)^T \rangle$$

- Since truth ( $x^t$ ) is not known, it needs to be estimated
- Common methods for estimating BE
  - Innovation Method
  - NMC Method:  $(x - x^t) \approx (x^{t1} - x^{t2})$   
(Forecast differences valid for same time)
  - Ensemble Method:  $(x - x^t) \approx (x^{ens} - \langle x^{ens} \rangle)$   
(Ensemble - Ensemble mean)
  - Flow dependent (adaptive approach)

# Properties of BE

- **B** matrix is square and symmetric. Thus, its eigenvalues are all real and eigenvectors are mutually orthogonal
- It is positive semi-definite. Thus, its eigenvalues are all non-negative. It is very important property because without this minimum of the cost function may not exist
- It consists of correlation (**C**) and variance parts ( $\Sigma$ ),  $\mathbf{B} = \mathbf{C}\Sigma$
- If **V** is an orthogonal transform matrix ( $\mathbf{V}^T\mathbf{V} = \mathbf{I}$ ) transforming any vector **X** to **U** ( $\mathbf{U} = \mathbf{VX}$ ), then the background error for **X** (**B**) and **U** will be related as  $\mathbf{B}^u = \mathbf{V}^T \mathbf{B} \mathbf{V}$
- A special representation of **B** is the eigen-representation, where **B<sup>u</sup>** is diagonalized. Eigenvectors of **B** forms the columns of **V** and the eigenvalues of **B** are the diagonal elements of **B<sup>u</sup>**

## Role of BE

- **B** spreads out information, both vertically & horizontally in space with proper weights to observations and FG. This effect may be understood by introducing a single observation of one element of  $x$ , say  $k$ th element, in the analysis equation

$$x^a = x^b + BH^T(HBH^T + R)^{-1}[y^o - H(x^b)]$$

In this case all the elements of  $H$  &  $H$  are zero except  $k$ th element which is = 1 and  $y^o = y$ ;  $R = \sigma^2$  & so the analysis equation is

$$x_l^a = x_l^b + B_{lk} \frac{y - x_k^b}{B_{kk} + \sigma^2}$$

Thus non-zero off-diagonal terms for  $B$  leads to analysis increment for  $l$ th element

- In data assimilation, this is not the only mechanism of spreading the information. Observation operators ( $H$  &  $H$ ) also does this job
- If  $\sigma^2 \ll B_{kk}$ ;  $x_k^a \approx y$  and if  $\sigma^2 \gg B_{kk}$ ;  $x_k^a \approx x_k^b$

## Role of BE

**Contd.**

- **B** matrix spreads information between variables and imposes balance
- Since **B** is the last operator in the analysis equation, the analysis increments lies in the subspace of **B**.
- **B** provides a means by which observations can act in synergy. **B** allows observations to reinforce each other in a way that improves the analysis to a degree that is greater than their individual contributions.
- **B** is used for preconditioning the analysis equation.

# How BE is represented in WRFDA?

- It is represented with a suitable choice of  $\mathbf{U}$  as follows

$$\mathbf{B} = \mathbf{U}^T \mathbf{U} \quad \text{with} \quad \mathbf{U} = \mathbf{U}_p \mathbf{U}_v \mathbf{U}_h$$

$\mathbf{U}_h$  Horizontal Transform

$\mathbf{U}_v$  Vertical Transform

$\mathbf{U}_p$  Physical Transform

- Horizontal transformation ( $\mathbf{U}_h$ ) is via
  - Regional ----- Recursive filters
  - Global ----- Power spectrum
- Vertical transformation ( $\mathbf{U}_v$ ) is via EOF's
- Physical transformation ( $\mathbf{U}_p$ ) depends upon the choice of the analysis control variable

# How BE is represented?

**Contd.**

- Size of B is typically of the order of  $10^7 \times 10^7$
- It is reduced by designing the analysis control variables in such a way that cross covariance between these variables are minimum
- Currently, analysis control variables for WRFDA are the amplitudes of EOF's of

stream function ( $\Psi$ )

Unbalanced part of velocity potential ( $X_u$ )

Unbalanced part of temperature ( $T_u$ )

Relative Humidity ( $q$ )


Unbalanced part of surface pressure ( $p_{s\_u}$ )

- With this choice of analysis control variables off-diagonal elements of BE is very small and thus its size typically reduces to the order of  $10^7$



# How BE is represented?

*Contd.*




# Components of BE


- Regression Coefficient for balanced part of Velocity potential, Temperature and Surface pressure
- Eigen vectors and Eigen values for stream function, unbalanced velocity potential, unbalanced temperature and moisture field
- Lengthscales for regional
- Power spectrum for global option

# Impact of BE on Minimization

Cost function minimization for CONUS 200 Km domain




Gradient function for CONUS 200 Km domain




**Good BE**

Cost function minimization for CONUS 200 Km domain




Gradient function for CONUS 200 Km domain



**Bad BE**


# Impact of BE on Temperature forecast

12 hr f/c bias/RMSE for Sound T




# Impact of BE on Temperature forecast

24 hr f/c bias/RMSE for Sound T



# Impact of BE on Wind (U Comp.) forecast

12 hr f/c bias/RMSE for Sound U-comp




Exp A: 6 Hr cycling with old BE

Exp B: 6 Hr cycling with new BE

# Impact of BE on Wind (U Comp.) forecast

24 hr f/c bias/RMSE for Sound U-comp



# WRFDA “gen\_be” utility:

- It resides in WRFDA under “var” directory
- Computes various components of BE statistics
- Designed both for NMC and Ensemble methods
- It consists of five stages
- Basic goal is to estimate the error covariance in analysis control variable space (Coefficients of the EOF's for  $\Psi$ ,  $X_u$ ,  $T_u$ ,  $rh$  and  $p_{s\_u}$ ) with input from model space ( $U$ ,  $V$ ,  $T$ ,  $q$  &  $P_s$ )

# “gen\_be” - Stage0

- Computes ( $\Psi$  ,  $X$ ) from ( $u, v$ )
- Forms desired differences for the following fields

$\Psi$  - Stream Function  
 $X$  - Velocity potential  
 $T$  - Temperature  
 $q$  - Relative Humidity  
 $p_s$  - Surface Pressure

## “gen\_be” - Stage1

- Reads “gen\_be\_stage1” namelist
- Fixes “bins” for computing BE statistics
- Computes “mean” of the differences formed in stage0
- Removes respective “mean” and forms perturbations for

Stream Function	$(\psi')$
Velocity potential	$(x')$
Temperature	$(T')$
Relative Humidity	$(q')$
Surface Pressure	$(p_s')$

## “gen\_be” - Stage2 & 2a

- Reads “gen\_be\_stage2” namelist
- Reads field written in stage1 and computes covariance of the respective fields
- Computes regression coefficient & balanced part of  $X$ ,  $T$  &  $p_s$

$$X_b = C \Psi'$$

$$T_b(k) = \sum_l G(k,l) \Psi'(l)$$

$$p_{s,b} = \sum_l W(k) \Psi'(k)$$

- Computes unbalanced part

$$X_u' = X' - X_b$$


$$T_u' = T' - T_b$$

$$p_{s,u}' = p_s' - p_{s,b}$$


# WRFDA Balance constraints

- WRFDA imposes statistical balanced constraints between
  - Stream Function & Velocity potential
  - Stream Function & Temperature
  - Stream Function & Surface Pressure
- How good are these balanced constraints?


$$\langle \chi_b \bullet \chi \rangle / \langle \chi \bullet \chi \rangle$$



$$\langle T_b \bullet T \rangle / \langle T \bullet T \rangle$$



$$\langle p_{sb} \bullet p_s \rangle / \langle p_s \bullet p_s \rangle$$



Computed based on KMA global model

## “gen\_be” - Stage3

- Reads “gen\_be\_stage3” namelist
- Removes mean for  $X_u'$ ,  $T_u'$  &  $p_{s_u'}$
- Computes eigenvectors and eigen values for vertical error covariance matrix of  $\psi'$ ,  $X_u'$ ,  $T_u'$  &  $q$
- Computes variance of  $p_{s_u'}$
- Computes eigen decomposition of  $\psi'$ ,  $X_u'$ ,  $T_u'$  &  $q$

## “gen\_be” - Stage4

- Reads “gen\_be\_stage4” namelist
- For each variable & each eigen mode, for regional option computes “lengthscale (s)”

$$B(r) = B(0) \exp\{-r^2 / 8s^2\}$$

$$y(r) = 2\sqrt{2}[\ln(B(0)/B(r))]^{1/2} = r/s$$

- For global option, computes “power spectrum ( $D_n$ )”

$$D_n = \sum_{m=-n}^n (F_n^m)^2 = (F_n^0)^2 + 2 \sum_{m=1}^n \left[ (\text{Re}(F_n^m))^2 + (\text{Im}(F_n^m))^2 \right]$$

# Single observation test

- Through single observation test, one can understand
  - structure of BE
  - It identifies the “shortfalls” of BE
  - It gives a broad guidelines for tuning BE

*Basic concept:*

Analysis equation:  $x^a = x^b + BH^T(HBH^T + R)^{-1}[y^o - H(x^b)]$

Set single observation (U,V,T etc. ) as follows:

$$[y^o - H(x^b)] = 1.0 \quad ; \quad R = I$$

Thus,

$$x^a - x^b = B * \text{constant delta vector}$$

# How to activate Single obs test (PSOT)?

“single obs utility” or “psot” may be activated by setting the following namelist parameters

`num_pseudo = 1`

`pseudo_var = “Variable name” like “U”, “T”, “P”, etc.`

`pseudo_x = “X-coordinate of the observation”`


`pseudo_y = “Y-coordinate of the observation”`

`pseudo_z = “Z-coordinate of the observation”`

`pseudo_val = “Observation value”, departure from FG”`

`pseudo_err = “Observation error”`

# Single Obs (U) test with different BE



# How to perform tuning of BE?

- Horizontal component of BE can be tuned with following namelist parameters

**LEN\_SCALING1 - 5** (Length scaling parameters)

**VAR\_SCALING1 - 5** (Variance scaling parameters)


- Vertical component of BE can be tuned with following namelist parameter

**MAX\_VERT\_VAR1 - 5** (Vertical variance parameters)

# Results with BE Tuning




No tuning

PSOT - u



Len\_scaling1 & 2 = 0.25

PSOT - u



## Some latest features in WRFDA V3.3

- Generation of multivariate background errors (cv\_options=6)

Declare “cv\_options=6” in the wrapper

Execute “gen\_mbe.ksh”

- Wavelet representation of BE

Declare USE\_RF=.false.

- Computation of BE for NCEP GSI applications

Execute “gen\_be\_gsi.ksh”

# Upcoming new features

- New method for computing horizontal lengthscale

$$L = \left\{ \frac{8 * \text{Variance}(X)}{\text{Variance}\{\nabla^2(X)\}} \right\}^{1/4}$$

- Inclusion of BE for cloud hydrometeors
- Implementation of Holm (2002) type BE for moisture variables

Stand alone branch of “gen\_be”

# Multivariate formulation of BE

- New set of analysis control variables have been designed

$$\chi_b(i,j,k) = \alpha_{\chi\psi} * \psi(i,j,k)$$


$$T_b(i,j,k) = \sum_{l=1}^{N_k} \alpha_{T\Psi}(i,j,k,l) * \psi(i,j,k,l) + \sum_{l=1}^{N_k} \alpha_{T\chi_u}(i,j,k,l) * \chi_u(i,j,l)$$

$$Q_b(i,j,k) = \sum_{l=1}^{N_k} \alpha_{Q\Psi}(i,j,k,l) * \psi(i,j,l) + \sum_{l=1}^{N_k} \alpha_{Q\chi_u}(i,j,k,l) * \chi_u(i,j,l) + \\ + \sum_{l=1}^{N_k} \alpha_{QT_u}(i,j,k,l) * T_u(i,j,l) + \sum_{l=1}^{N_k} \alpha_{ps_uQ}(i,j,l) * ps_u(i,j)$$

$$P_s(i,j) = \sum_{l=1}^{N_k} \alpha_{Ps\Psi}(i,j,l) * \psi(i,j,l) + \sum_{l=1}^{N_k} \alpha_{Ps\chi_u}(i,j,l) * \chi_u(i,j,l)$$

Indexes i,j and k are corresponding to West-East, North-South and vertical sigma levels respectively, N<sub>k</sub> is the number of sigma levels and α is the regression coefficient between the variables indicated in its subscript.

# Single Obs (Moisture) test



Old BE

New BE

# Practice Session 3

- **Compilation of “gen\_be” utility**
- **Generation of BE statistics**
- **Familiarization with various graphical utilities to display “gen\_be” diagnostics**
- **Running single observation tests to understand the structure of BE**
- **BE error tuning**

# Generation of BE

- “gen\_be\_wrapper.ksh” script for generating BE for “CONUS” at 60 Km domain with:

Grid Size : 90 x 60 x 41

BE Method : NMC Method

Data Input : February, 2008 forecasts, both from 00 & 12 UTC IC

Basic environment variables that needs to be set are:

- Gen\_be executables location (WRFVAR\_DIR)
- Forecast input data (FC\_DIR)
- Run directory (BE\_DIR)
- Data Range (START\_DATE, END\_DATE)

“gen\_be” wrapper script basically executes “var/scripts/gen\_be/gen\_be.ksh” script

# Gen\_be diagnostics

- “gen\_be” creates various diagnostic files which may be used to display various components of BE statistics.
- Important files are:

Eigen vectors:      **fort.174, fort.178, fort.182, fort.186**

Eigen values:      **fort.175, fort.179, fort.183, fort.187**

scalelength:      **fort.194, fort.179, fort.183, fort.187**

Correlation between  $x_u$  &  $x_b$  (**chi\_u.chi.dat**)

Correlation between  $T_u$  &  $T_b$  (**T\_u.T.dat**)

Correlation between  $p_{s_u}$  &  $(ps_u.ps.dat)$

Important Strings that needs to be defined in the wrapper script

**“var/script/gen\_be/gen\_be\_plot\_wrapper.ksh”**

**BE\_DIR --- gen\_be Run directory**

# How to run Single Observation Test ?

- Familiarization with single observation “wrapper” script (“da\_run\_suite\_wrapper\_con200.ksh”) to run Single Observation test
- Key parameters are
  - Type of observation (**pseudo\_var**)
  - Obs co-ordinates (**pseudo\_x**, **pseudo\_y** & **pseudo\_z**)
  - Observation value (**pseudo\_val**)
  - Observation error (**pseudo\_err**)
- Display analysis increments to understand BE structure

# BE tuning

- Understand the role of BE-tuning parameters through namelist options

**LEN\_SCALING1 - 5** (Length scaling parameters)

**VAR\_SCALING1 - 5** (Variance scaling parameters)

**MAX\_VERT\_VAR1 - 5** (Vertical variance parameters)

**Note:** If BE is available for the same domain configuration then it's tuning is not required